


A50CK4470AA00K


Aliases (50CK4470AA00K)

A50, Film, Metallized Polyester, Automotive Grade, 4.7 uF, 10%, 30 VAC, 50 VDC, 85°C

FRONT VIEW



SIDE VIEW



Click [here](#) for the 3D model.

Dimensions

D	8.5mm MAX
L	20.5mm MAX
LL	40mm +/-5mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	750

General Information

Series	A50
Dielectric	Metallized Polyester
Style	Axial
Features	Automotive Grade
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
Component Weight	2.1g
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C. maxK0 = 200.

Specifications

Capacitance	4.7 uF
Capacitance Tolerance	10%
Voltage AC	30 VAC
Voltage DC	50 VDC, 37.5 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz
Insulation Resistance	212.8 MOhms
Max dV/dt	2 V/us
Inductance	7 nH