





SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/10/2018

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	DEOXIT® FLUX WASH
1.2	Chemical Name:	See ingredients listed in section 3
1.3	Synonyms:	DeoxIT® FLUX Wash (PN DCC-V510)
1.4	Trade Names:	DeoxIT® FLUX Wash PART NOS: Part No. DFW-V711 (156 grams); Part No. DFW-V710 (284 grams)
1.5	Product Uses & Restrictions:	Cleaning Compound
1.6	Distributor's Name:	CAIG Laboratories, Inc.
1.7	Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN205206)
1.9	Business Phone / Fax:	+1 (800) 224-4123

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER; MAY BURST IF HEATED. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Aerosol 1, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3	 
2.2	Label Elements:	<p>Hazard Statements (H): H222 – Extremely flammable aerosol. H229 – Pressurized container; may burst if heated. H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H336 – may cause drowsiness or dizziness.</p> <p>Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on an open flame or other ignition source. P233 – Keep container tightly closed. P251 – Do not pierce or burn, even after use. P261 – Avoid breathing fume/gas/mist/vapor/spray. P264 – Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective gloves/ eye protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN: Wash with plenty water and soap. P321 – For specific treatment, see Section 4 of this Safety Data Sheet. P332+P313 – If skin irritation occurs: get medical advice/attention. P362 +P364 - Take off contaminated clothing and wash before reuse. P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 – Call a POISON CENTER/doctor if you feel unwell. P403+P233- Store in a well-ventilated place. Keep container tightly closed. P405 – Store locked up. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	
2.3	Other Warnings:	In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. KEEP OUT OF REACH OF CHILDREN.	


3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0	NA	265-151-9	60-100	100	NA	100	NA	NA	NA	NA	NA	NA	SKIN
DIFLUOROETHANE (R-152A)	75-37-6	K14100000	200-866-1	10-30	1000	NA	1000	NF	NF	NA	NA	NA	NA	SKIN
n-HEXANE	110-54-3	MN9275000	203-777-6	≤ 5.0	1800	NA	500	1760	NF	1800	3600	NA	NA	
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	≤ 2.0	1000	3000	1000	1800	NF	1000	1900	3300	NA	
METHANOL	67-56-1	PC1400000	200-659-6	≤ 1.0	200	250	(200)	262	NF	200	250	6000	NA	
2-PROPANOL	67-63-0	NT8050000	200-661-7	≤ 1.0	400	500	(400)	983	NF	400	500	2000	NA	
METHYL ISOBUTYL KETONE	108-10-1	SA9275000	203-550-1	≤ 1.0	50	75	(50)	205	NF	100	NF	500	NA	

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><u>Eyes:</u> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention.</p> <p><u>Skin:</u> Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>											
4.2	Effects of Exposure:	<p><u>Ingestion:</u> If product is swallowed, may cause nausea, vomiting and/or diarrhea.</p> <p><u>Eyes:</u> Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> None expected.</p>											
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p><u>Eyes:</u> Overexposure in eyes may cause redness, itching and watering.</p> <p><u>Skin:</u> Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.</p>											
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin.											
4.5	Chronic Health Effects:	Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis.											
4.6	Target Organs:	Eyes, Skin, Respiratory System.											
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).	<table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white; padding: 2px;">HEALTH</td> <td style="text-align: center; padding: 2px;">2</td> </tr> <tr> <td style="background-color: #FF0000; color: white; padding: 2px;">FLAMMABILITY</td> <td style="text-align: center; padding: 2px;">3</td> </tr> <tr> <td style="background-color: #FFA500; color: white; padding: 2px;">PHYSICAL HAZARDS</td> <td style="text-align: center; padding: 2px;">1</td> </tr> <tr> <td style="background-color: #000000; color: white; padding: 2px;">PROTECTIVE EQUIPMENT</td> <td style="text-align: center; padding: 2px;">B</td> </tr> <tr> <td style="padding: 2px;">EYES</td> <td style="padding: 2px;">SKIN</td> </tr> </table>	HEALTH	2	FLAMMABILITY	3	PHYSICAL HAZARDS	1	PROTECTIVE EQUIPMENT	B	EYES	SKIN
HEALTH	2												
FLAMMABILITY	3												
PHYSICAL HAZARDS	1												
PROTECTIVE EQUIPMENT	B												
EYES	SKIN												

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride).	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to cool unopened containers.	
5.3	Firefighting Procedures:	Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills.</p> <p><u>Small Spills:</u> Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container.</p> <p><u>Large Spills:</u> Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant.</p>
-----	---------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use.
7.3	Special Precautions:	Clean all spills promptly.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		N-HEXANE	1800	NA	500	1760	NF	1800	3600	NA	
		DIFLUOROETHANE (R-152A)	1000	NA	1000	NF	NF	NA	NA	NA	SKIN
		ETHANOL (SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		METHANOL	200	250	(200)	262	NF	200	250	6000	
		2-PROPANOL	400	500	(400)	983	NF	400	500	2000	
		METHYL ISOBUTYL KETONE	50	75	(50)	205	NF	100	NF	500	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
8.4	Eye Protection:	Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.									
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Colorless to pale yellow liquid
9.2	Odor:	Solvent-like odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	58- 64 °C (136.4-147.2 °F) (lowest component)
9.7	Flashpoint:	-17 °C (1.4 °F) (lowest component), TCC
9.8	Upper/Lower Flammability Limits:	LEL: 1.2 % / UEL: 6.7%
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA
9.11	Relative Density:	0.66
9.12	Solubility:	Negligible
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: 75%

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/10/2018

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product.		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	NA. This product contains less than 3% Dimethyl Sulfoxide (DMSO) per IP 346.		
11.6	Reproductive Toxicity:	WARNING: This product can expose you to chemicals including Hexane, Methanol and Methyl Isobutyl Ketone (MIKB), which are known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov .		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	WARNING: This product can expose you to chemicals including Hexane, Methanol and Methyl Isobutyl Ketone (MIKB), which are known to the State of California to cause cancer or other reproductive harm. For more information, go to www.P65Warnings.ca.gov .		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	<u>Methanol</u> : Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. <u>Methyl Isobutyl Ketone</u> : Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Low potential for adsorption in soil. Photolysis in the air.
12.2	Effects on Plants & Animals:	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Products covered by this SDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations:	U.S. EPA RCRA Hazardous Waste: D001 (Characteristic – Ignitability). California Waste Code: 331 (liquid concentrate).

14. TRANSPORTATION INFORMATION



The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020	
14.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	




15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Hexane</u> and <u>Methanol</u> substances subject to SARA Title III, Section 313 reporting requirements. This product contains <u>Methyl-Isobutyl Ketone (MIBK)</u> a substance subject to SARA Title III, Section 311 reporting.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2,270 kg (5000 lbs); <u>Methanol</u> : 2,270 kg (5,000 lbs.); <u>Methyl-Isobutyl Ketone (MIBK)</u> : 2,270 kg (5,000 lbs)
15.5	Other Federal Requirements:	Methanol and Methy-Isobutyl Ketone ingredients in this mixture are listed as Hazardous Air Pollutants (HAPs). None of the ingredients in this mixture are listed as a Priority Pollutant under the CWA. None of the ingredients in this mixture are listed as a Toxic Pollutant under the CWA.

15. REGULATORY INFORMATION – cont'd

15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol).	
15.7	State Regulatory Information:	<p><u>Ethanol</u> is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Pennsylvania Right-to-Know List (PA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ).</p> <p><u>Methanol</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA, WA and WI.</p> <p><u>Methyl Isobutyl Ketone</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA, WA and WI.</p> <p><u>Isopropanol</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA, and WA.</p> <p><u>Difluoroethane</u> can be found on the following state criteria lists: MA and NJ.</p> <p>No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p> WARNING: This product can expose you to chemicals including Hexane, Methanol and Methyl Isobutyl Ketone, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov.</p>	

16. OTHER INFORMATION

16.1	Other Information:	<p>DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER; MAY BURST IF HEATED. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Do not pierce or burn, even after use. Avoid breathing fume/gas/mist/vapor/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty water and soap. For specific treatment, see Section 4 of this Safety Data Sheet. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.</p> <p> WARNING: This product can expose you to chemicals including Hexane, Methanol and Methyl Isobutyl Ketone, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	<p>CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/</p>	
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLO	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₀₁ or TC, TC₀₁, LC₁₀, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment