



21XXXX515-XX
Code
Pin Number

2 Pin	P/N: 21002515-02	P/N: 21003515-02	P/N: 21004515-06
-------	------------------	------------------	------------------



- Specification:
1. Operation Temperature: $-45^{\circ}\text{C} \sim 105^{\circ}\text{C}$.
 2. Insulation Resistance: $100\text{M}\Omega$ at DC 500V.
 3. Contact Resistance: $<10\text{m}\Omega$.
 4. Withstand Voltage: 1500V AC.
 5. Operating Current: 5A.
 6. Operating Voltage: AC 110V.
 7. Waterproof Rate: IP67 (Mated).
 8. Connector: Nylon+GF, Black.
 9. Panel Nut: Nylon, Black.
 10. Gasket: Silicon, Gray.
 11. Male Pin: Copper Alloy Gold Plated.
 12. Torque Rate: $0.5 \sim 0.7\text{N}\cdot\text{m}$.
 13. RoHS Compliant.
 14. UL Compliant.
 15. Mating Cap P/N: 806-00028-00

Pin Assignments Front View



DESCRIPTION Mini Series Screw Type Front Mount With Male Pin(PCB)

TOLERANCE	±0.25	SCALE	4:5	SHEET	1 OF 1
.X	±0.15	REV	C1	SIZE	A4
.XX	±0.05	* : Inspection Item			
.XXX					
ANGLES	±1°				

CHOGORI

PART NO	21XXXX515-XX	DRAWN BY	Victory	DATE	2019/08/21
DWG NO		CHECKED BY	Ivon	DATE	2019/08/21
CUSTOMER		APPROVED BY	Ponson	DATE	2019/08/21

REV.	EN. NO.	DESCRIPTION	SIGN	DATE
C1	N/A	INITIAL DRAWING	Victory	2019/08/21