

NOTES:

1. MATERIALS AND FINISHES:

- BODY & COUPLING NUT - BRASS, TIN-NICKEL ALLOY PLATING
- CONTACT - BeCu, GOLD PLATING
- BULLET CONTACT - BRASS, GOLD PLATING
- INSULATOR - PTFE, NATURAL
- INSULATOR DISC - ULTEM, NATURAL
- RETAINING RING - PHOSPHOR BRONZE, NICKEL PLATING
- GASKET & O-RING - SILICONE RUBBER, RED
- FERRULE - COPPER, TIN-NICKEL ALLOY PLATING
- HEAT SHRINK TUBING - CROSSLINKED POLYOLEFIN, BLACK

2. ELECTRICAL:

- A. IMPEDANCE: 50 OHM
- B. FREQUENCY RANGE: DC - 6 GHz
- C. VSWR: 1.30 MAX.
- D. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS, MIN.

3. MECHANICAL:

- A. DURABILITY: 500 CYCLES MIN.
- B. TEMPERATURE RANGE: -40°C TO +85°C
- C. SALT SPRAY PER MIL-STD-202, METHOD 101, WITH FOLLOWING PARAMETERS:
 - 1) TEST CONDITION B
 - 2) 5% SALT SOLUTION
 - 3) CYCLE REPEATED TO 720 HOURS

4. PACKAGING:

- A. QUANTITY: SINGLE PACK
- B. MARKING: PACKAGING TO BE MARKED "AMPHENOL RF, 31-6923-EE AND DATE CODE"


5. CABLE ASSEMBLY INSTRUCTIONS:

- A. TRIM CABLE AS SHOWN.
- B. SLIDE HEAT SHRINK TUBING AND FERRULE ONTO CABLE.
- C. SLIDE INSULATOR DISC ONTO CABLE CENTER CONDUCTOR.
- D. SOLDER CABLE CENTER CONDUCTOR TO BULLET CONTACT.
- E. INSERT CABLE WITH DIELECTRIC ENTERING CONNECTOR AND BRAID OVER KNURL.
- F. CRIMP FERRULE OVER BRAID WITH 0.213" HEX DIE.
- G. APPLY HEAT SHRINK TUBING OVER FERRULE.
- H. HEAT SHRINK TUBING SHOULD FULLY (360 DEG) COVER THE BUMP ON BODY AND END WITHIN AREA "A".


6. RECOMMENDED COUPLING TORQUE : 4-6 IN-LBS.

7. SHOWS CABLE ENTRY DIMENSIONS.


REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	7-Jul-22	16314	SH



SCALE 1.000



RECOMMENDED CABLE STRIPPING DIMENSIONS



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE:
 <0.5mm = ±0.05mm [$<0.020 = \pm 0.002$]
 0.5 - 6mm = ±0.1mm [$>0.020 - 0.236 = \pm 0.004$]
 >6.00 - 30mm = ±0.2mm [$>0.236 - 1.181 = \pm 0.008$]
 >30.00 - 120mm = ±0.3mm [$>1.181 - 4.725 = \pm 0.012$]

MATERIAL: SEE NOTES
 ENGR.1: KARTHIK ENGR.2: WIKI DATE: 20-MAY-22

TITLE: TNC STR PLUG IP 67 FOR RG 58 CABLE EXTREME EXPOSURE
 SHEET NO. 2 OF 2 SCALE: 3.0:1.0

Amphenol RF
 DRAWING NO. 31-6923-EE
 ITEM NO. 31-6923-EE
 PART NO. 31-6923-EE
 REV: A

THIRD ANGLE PROJ.

REFERENCE: EAR# 11329

ANGLES = ±1°

ENGR.1: KARTHIK ENGR.2: WIKI DATE: 20-MAY-22

SHEET NO. 2 OF 2 SCALE: 3.0:1.0

REV: A