## **HellermannTyton**

## **Specification Sheet**

Part Number: 156-02723



One-piece ratchet closure allows for easy installation during pre- or final assembly.

Easy release feature simplifies quick adjustments and maintenance.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

3M<sup>™</sup> VHB<sup>™</sup> adhesive on base creates an incredible bond with mountine surface.

Inline Ratchet Clamp, 0.50" - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/box

Article Number 156-02723

Type IRCBMB5A

Color Black (BK)

Quantity Per bag

_				-	_							
ם	rn	<b>~</b> I	114	rt.	- 11	es	r	rı	n	tı	$\mathbf{a}$	'n
	v	u	и١	Ŀι	$\boldsymbol{\omega}$	CO	u		v	LI	u	

The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

**Short Description** 

Inline Ratchet Clamp, 0.50" - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/box

**Global Part Name** 

IRCBMB5A-PA66HIRHSUV-BK

100.0

Minimum Tensile Strength (Imperial)

Minimum Tensile Strength (Metric) 445.0

Length L (Imperial) 1.37

Length L (Metric) 34.8

Fixation Method Adhesive

Width W (Imperial) 1.37

Width W (Metric) 34.9

**Bundle Diameter Min (Imperial)** 0.50

Bundle Diameter Min (Metric) 12.70

**Bundle Diameter Max (Imperial)** 0.77 **Bundle Diameter Max (Metric)** 19.56 Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) **Material Shortcut** PA66HIRHSUV Adhesive Acrylic **Flammability** UL 94 HB **Operating Temperature** -40°F to +221°F (-40°C to +105°C) **ROHS Compliant** Yes Package Quantity (Imperial) 25 Package Quantity (Metric) 25