

1

2

3


4

5

6

7

A



2.54±0.10

B

5.00±0.15

C

1.70

Ⓢ3.8

D

Ⓢ5.0

E

F

1.20

Ⓢ2.45±0.15

A

Ⓢ6.00±0.15

Ⓢ13.60

5.40

NOTES:

1. Insulation: Nylon 66, UL94V-0
2. Contact : Brass
- ⑧⑥ 3. Plated: Gold Flash or Tin over Nickel
4. Current Rating: 3A Max
5. Dielectric Voltage: 1000V rms / 1 minute
6. Insulation Resistance: 1000M ohm Min.
7. Contact Resistance: 30m ohm Max.
8. Operating and Storage Temperature: -40°C ~ +105°C
- ③ 9. Mating Cycles: 10 Min.

⑧⑤ AKSPLTx xx

Color:
RED
BLACKContact Area Plating:
G: Gold Flash
Z: Tin plated

A

B

C

D

E

F

RoHS compliant
Unit:mm

Scale Free

⑧TOLERANCE

X. ±0.35

X.X ±0.25

X.XX ±0.20

X.XXX ±0.15

DIM TOL

Angle TOL

⑧

Update the dimension and tolerance

25.07.2022

Peter

Date

Name

Description. Jumper Connector

⑦

Change the plant

20.04.2022

Winnie

Drawn

21.03.2007

Hellwig

⑥

Update plated information

20.08.2015

Ray

Approved

25.07.2022

Peter

ASSMANN WSW-No. ④ AKSPLTx BLACK
⑤ AKSPLTx RED

⑤

Add the order code: AKSPLTx RED

13.01.2014

Winnie

④

Order code correction

07.01.2014

Winnie

③

Update

07.06.2013

Winnie

Id.

Modification

Date

Name

ASSMANN
WSW components

Drawing-No.

ASS 0327 CO

rev08

Customer-No.

SHEET
1 / 1

G

H

1

2

3

4

5

6

7