

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A		INITIAL	12APR2016	YC	CW
B		ECR-21-111798	02SEP2021	WQR	CW

M4 THREAD
RECOMMENDED
TIGHTENING TORQUE 1.2Nm

4X M3 THREAD, RECOMMENDED
TIGHTENING TORQUE 0.5Nm

PANEL CUT FOR INSERTS FOR USE
WITHOUT HOODS/ HOUSINGS


NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 500V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
CONTACT TYPE: CRIMP CONTACT
- CONTACTS NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20300X10XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 500V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C \sim +125^{\circ}C$
接线范围: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
接线类型: 冷压接
- 端子需要单独订购。
(订货号参考图面: T20300X10XX000)

T2050802101-000	HEEE-040-M 41-80 HEEE-040公插 41-80
PART NUMBER 料号	PART DESCRIPTION 描述

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 12APR2016 YORK CHEN		 TE Connectivity NAME HEEE-040-M 41-80			
DIMENSIONS: mm		CHK 12APR2016 KYLE ZENG					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 12APR2016 CHRIS WANG					
0 PLC \pm - 1 PLC \pm - 2 PLC \pm - 3 PLC \pm - 4 PLC \pm - ANGLES \pm - FINISH \pm -		PRODUCT SPEC 108-137068 APPLICATION SPEC 108-137068 WEIGHT -					
MATERIAL -		Customer Drawing		SIZE A3	CAGE CODE 00779	DRAWING NO T2050802101000	RESTRICTED TO -
				SCALE 1:1	SHEET 1 OF 1	REV B	

1470-19 (3/13)