



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.91±0.2      |
| PP                  | 6.15±0.2      |
| R1                  | 38.1          |
| R2                  | 34.93         |
| S                   | 46±0.3        |
| V                   | 20.07+0/-1.25 |
| W                   | 2.1/3.2       |
| Z                   | 31.5 Max      |
| VV THREAD           | M37x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D025Z90SDL**

|                |   |                                |  |
|----------------|---|--------------------------------|--|
| A              | 10-10-2016                              | First Release                  |  |
| ISS            | DATE                                    | Latest modification - by       | MOD N°   |
| Designed By:   |   | Date:                          | <b>CUSTOMER DRAWING</b>  |
| <b>TITLE</b>   | <b>Aluminium Receptacle 8D series</b>   |                                |  |
| SCALE          |   | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>  |
| NA             |   |                                | This document is the property of SOURIAU<br>it must not be reproduced or communicated without permission |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                  |                                |  |
| FORMAT         | <b>SOURIAU DRG N°<br/>8D025Z90SDL-C</b> |                                | SHEET<br>1/2   |

BASIC SERIES: 8D 0 - 25 Z 90 S D L

SHELL TYPE : Square Flange Receptacle Delivered W/O Contacts

CONTACT TYPE : Standard Crimp Contact ORIENTATION : D

SHELL SIZE : 25 CONTACT TYPE : SOCKET(500 Matings)

PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 25-50

Contact Layout



(Inactive for new design for MIL-DTL-38999. For new design, use arrangement no. 25-91.)

| Contacts<br>(Insert arrangement 25-90) |              |              |                     |              |              |
|--|--------------|--------------|---------------------|--------------|--------------|
| Contact position ID                    | Location     |              | Contact position ID | Location     |              |
|  | X-axis (mm)  | Y-axis (mm)  |                     | X-axis (mm)  | Y-axis (mm)  |
| A                                      | +065 (1.65)  | +533 (13.54) | a                   | +404 (10.26) | +125 (3.18)  |
| B                                      | +275 (6.99)  | +466 (11.84) | b                   | +437 (11.10) | +000 (0.00)  |
| C                                      | +420 (10.67) | +337 (8.56)  | c                   | +404 (10.26) | -125 (3.18)  |
| D                                      | +490 (12.45) | +227 (5.77)  | d                   | +314 (7.98)  | -221 (5.61)  |
| E                                      | +531 (13.49) | +093 (2.36)  | e                   | +245 (6.22)  | -337 (8.56)  |
| F                                      | +531 (13.49) | -093 (2.36)  | f                   | +136 (3.45)  | -424 (10.77) |
| G                                      | +490 (12.45) | -227 (5.77)  | g                   | +000 (0.00)  | -395 (10.03) |
| H                                      | +420 (10.67) | -337 (8.56)  | h                   | -136 (3.45)  | -424 (10.77) |
| J                                      | +275 (6.99)  | -466 (11.84) | j                   | -245 (6.22)  | -337 (8.56)  |
| K                                      | +065 (1.65)  | -533 (13.54) | k                   | -314 (7.98)  | -221 (5.61)  |
| L                                      | -065 (1.65)  | -533 (13.54) | l                   | -404 (10.26) | -125 (3.18)  |
| M                                      | -275 (6.99)  | -466 (11.84) | m                   | -437 (11.10) | +000 (0.00)  |
| N                                      | -420 (10.67) | -337 (8.56)  | n                   | -404 (10.26) | +125 (3.18)  |
| P                                      | -490 (12.45) | -227 (5.77)  | p                   | -314 (7.98)  | +221 (5.61)  |
| R                                      | -531 (13.49) | -093 (2.36)  | r                   | -245 (6.22)  | +337 (8.56)  |
| S                                      | -531 (13.49) | +093 (2.36)  | s                   | -136 (3.45)  | +424 (10.77) |
| T                                      | -490 (12.45) | +227 (5.77)  | t                   | +000 (0.00)  | +395 (10.03) |
| U                                      | -420 (10.67) | +337 (8.56)  | u                   | +097 (2.46)  | +265 (6.73)  |
| V                                      | -275 (6.99)  | +466 (11.84) | v                   | +180 (4.57)  | +000 (0.00)  |
| W                                      | -065 (1.65)  | +533 (13.54) | w                   | +097 (2.46)  | -265 (6.73)  |
| X                                      | +136 (3.45)  | +424 (10.77) | x                   | -097 (2.46)  | -265 (6.73)  |
| Y                                      | +245 (6.22)  | +337 (8.56)  | y                   | -180 (4.57)  | +000 (0.00)  |
| Z                                      | +314 (7.98)  | +221 (5.61)  | z                   | -097 (2.46)  | +265 (6.73)  |
|  |              |              | AA                  |              |              |

| Shell size | Arrangement no. | Number of contacts | Size of contacts | Service rating | Contact location | Standard contact |               |
|------------|-----------------|--------------------|------------------|----------------|------------------|------------------|---------------|
|            |                 |                    |                  |                |                  | Pin              | Socket        |
| 25         | -90             | 2                  | 8 (see note)     | Twinax         | W, Z             | M39029/90-529    | M39029/91-530 |
|            |                 | 4                  | 16               |                |                  | M39029/56-364    | M39029/56-352 |
|            |                 | 40                 | 20               | All others     | M39029/56-363    | M39029/56-351    |               |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 42.47 min  |
| ØAA | 37.69 min  |
| R1  | 38.1       |
| ØT  | 3.81 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D025Z90SDL

|                |                                     |                                |   |
|----------------|-------------------------------------|--------------------------------|---|
| A              | 10-10-2016                          | First Release                  |   |
| ISS            | DATE                                | Latest modification - by       | MOD N°  |
| Designed By:   |                                     | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series      |                                |   |
| SCALE          |                                     | General linear Tolerances: ±-- | NPRDS / PROJECT   |
| NA             |                                     |                                | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>              |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D025Z90SDL-C</b> |                                | SHEET 2/2   |