

G83-6644

Full QWERTY Keyboard with Smart Card Reader



**Full QWERTY Keyboard
with Integrated Smart
Card Reader**

Main Applications

Rack Mount Systems
Airlines
Education/Schools
Banking
Medical Equipment
Automotive Equipment
POS/POT
Office/Data Entry
White Box PCs
Field Services
Test Equipment
Kiosk Applications
POS/POT
Manufacturing
Transport

Key Features

- USB 2.0
- Secure PIN entry (class 2 reader)
- PC/SC smart card reader
- CT-API support
- Protocols T=0, T=1, S=8, S=9 and S=10
- EMV 2000 Terminal level 1 approved
- CCID compliant
- Compliant with ISO 7816
- Individual and easy key assignment due to our Keym@n Software with new, comfort functions
- CAC certified and FIPS 201 certified

Main Part Numbers

G83-6644LUAx-0

Light grey housing, 105 keys, and DE, FR, GB, ES, IT, RU, CH, BE country versions

G83-6644LUAx-2

Black housing, 105 keys, and DE, FR, GB, ES, IT, RU, CH, BE country versions

G83-6644LUAEU-0

Light grey housing, 104 keys, and US with € country versions

G83-6644LUAEU-2

Black housing, 104 keys, and US with € country versions

The xx in the order description defines the country version.

BE Belgium
CH Switzerland
DE Germany
DK Denmark
ES Spain
EU US English/ international €
FR France
GB English (UK)
IT Italy
NO Norway
PO Portugal
SF Sweden/Finland
US US-English

G83-6644

Full QWERTY Keyboard with Smart Card Reader

Main Part Numbers

G83-6644



Technical Data

Interface

USB full speed

Current Consumption

max. 100 mA

Cable Length

approx. 1.8 m

Number of Keys

104 = US Layout with Windows Vista™ keys

105 = EU Layout with Windows Vista™ keys

Weight

approx. 680 g (without packaging)

approx. 840 g (with packaging)

Operating System

Windows 98, ME, 200, XP, XP 64Bit, CE, Linux, Mac OS X, Vista

Smart Card Speed:

412,903 bps

Smart Card Clock:

4.8 MHz

Storage Temperature

-20°C to 60°C

Operating Temperature

0°C to 50°C

Agency Approvals

FCC, GS, CE, c-tick, GHOST-R, VCCI

EMV 2000 level 1

Microsoft Windows™ 2000, XP, Vista

Dimensions

approx. 458 x 170 x 52 mm (keyboard)

approx. 495 x 200 x 55 mm (packaging)

Packaging Units

53 keyboards per master carton

106 keyboards per pallet

Keyswitch Lifetime

20 million operations

System Requirements

USB Connection

Insertion Cycles

approx. 100,000

Delivery Volume

1 SmartBoard keyboard, 1 Manual, Brown Gift Box

Warranty

2 Years

Contact

Call, fax or visit our website for more information.

Last Update: 2/15/10

ZF Electronics Corporation

11200 88th Avenue
Pleasant Prairie, WI 53158

Phone: 262.942.6500

Web: www.cherrycorp.com

E-Mail: keyboardsupport@zf.com

Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 ZF Electronics Corporation