



Click [here](#) for the 3D model.

| Dimensions |                  |
|------------|------------------|
| W          | 5.59mm MAX       |
| H          | 7.37mm MAX       |
| T          | 2.79mm MAX       |
| S          | 4.57mm +/-0.64mm |
| LL         | 19.1mm MIN       |
| F          | 0.41mm MAX       |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 500       |

| General Information |                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Series              | T370                                                                                                                         |
| Dielectric          | MnO2 Tantalum                                                                                                                |
| Style               | Radial Molded                                                                                                                |
| Description         | Radial, Solid Tantalum, Micro Miniature                                                                                      |
| Features            | Micro Miniature                                                                                                              |
| RoHS                | No                                                                                                                           |
| Prop 65             | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number         | a3b4e2e1-63ea-439e-a89a-743225502a7d                                                                                         |
| Termination         | Lead (SnPb)                                                                                                                  |
| AEC-Q200            | No                                                                                                                           |
| Construction        | Molded                                                                                                                       |

| Specifications        |                                                      |
|-----------------------|------------------------------------------------------|
| Capacitance           | 4.7 uF                                               |
| Capacitance Tolerance | 10%                                                  |
| Voltage DC            | 35 VDC (85C), 23 VDC (125C), 0.35 VDC (125C Reverse) |
| Temperature Range     | -55/+125°C                                           |
| Dissipation Factor    | 6%                                                   |
| Resistance            | 3 Ohms (100kHz)                                      |
| Leakage Current       | 2 uA                                                 |