



Side entry hoods with knurled screws

| Identification | No. of contacts | Part number | Drawing | Dimensions in mm |
|----------------|-----------------|-------------|---------|------------------|
|----------------|-----------------|-------------|---------|------------------|

D-Sub

| | | | | | | | |
|---|--|----------------|--|------------------------|----------------|-------------------------|--|
| Hood ¹⁾ grey thermoplastic RAL 7032 | 9 | 09 67 009 0571 | <p>Upper hood part</p> <p>9 contacts</p> | <p>Lower hood part</p> | | | |
| | 15 | 09 67 015 0571 | | | | | |
| | 25 | 09 67 025 0571 | | | | | |
| | 37 | 09 67 037 0571 | | | | | |
| | 50 | 09 67 050 0571 | | | | | |
| | grey thermoplastic with internal tin-plate screening | 9 | | | 09 67 009 0573 | <p>15 – 50 contacts</p> | |
| | | 15 | | | 09 67 015 0573 | | |
| | | 25 | | | 09 67 025 0573 | | |
| | | 37 | | | 09 67 037 0573 | | |
| | | 50 | | | 09 67 050 0573 | | |
| 9-37 way for packaging density of 3 TE (15.24 mm) | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

| | a max. | b min. | c | d | e | f |
|----|-----------|-----------|-------|-------|------|------|
| 15 | 39.62 | 28.40 | 13.00 | 14.00 | 1.00 | 7.50 |
| 25 | 53.52 | 42.20 | 13.00 | 14.00 | 1.00 | 7.50 |
| 37 | 69.80 | 58.65 | 13.00 | 14.00 | 1.00 | 7.50 |
| 50 | 67.41 | 56.18 | 16.00 | 17.50 | 1.50 | 9.50 |

| | | | |
|--|------|------------------------------|--|
| Knurled screw Thread UNC Thread M3 | 9-50 | 09 67 000 9971 ²⁾ | |
| | | 09 67 001 9965* | |
| Thread UNC Thread M3 | 9-50 | 09 67 001 9978 | |
| | | 09 67 001 9977 | |

Grey head / Nickel plated steel

Full metal part

| | | | |
|-------------------------------------|-----------------|-----------------|--|
| Tooling for assembly of hoods | | | |
| | Top part | 09 99 000 0215* | |
| Bottom part | 09 99 000 0216* | | |

05
146

* Not normally kept in stock
¹⁾ Order knurled screw separately
²⁾ 9 way 1 per hood – 15-50 way 2 per hood

³⁾ Screw driver type ISO PH 1 for philips screw No 1 ISO norm 4757
 Operating temperature for all hoods on this page: -30 °C ... +100 °C