

EUROPEAN STANDARDIZED CABLES



H07RN-F Heavy duty neoprene jacketed harmonized cordage 450/750 volts

HAR CE

H07RN-F is recommended for use in dry, humid or moist environments. It is designed for medium mechanical stresses, eg. for industrial and agricultural workshops appliances, large boiling installations, heating plates, inspection lamps, electrical tools such as drills, circular saws, domestic electric tools, and also for transportable motors or machines on building sites or in agricultural workings and is suitable for the wiring of constructional components in lifting appliances, machinery, etc.

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, class 5
Insulation:	synthetic rubber, Type E14
Color Code:	acc. to HD 308
Stranding:	from 2 conductors stranded in layers
Jacket material:	synthetic rubber, EM2
Jacket color:	black

Technical data:

Nominal voltage:	Uo/U 450/750 V
Testing voltage U:	2500 V
Min. bending radius:	6 x O.D.
Temperature range:	-25/+60°C
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

Outstanding features:

- ▶ harmonized to European standards
- ▶ high mechanical loading capacity
- ▶ UV resistant

item no.	no. of conductors incl. ground	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
▶ 18 AWG (≈ 30/32) • 1.00 mm²				
39550210	2	0.327	8.3	67
39550310	3	0.350	8.9	81
39550410	4	0.382	9.7	87
39550510	5	0.433	11.0	114
▶ 16 AWG (≈ 27-29/30) • 1.50 mm²				
39550215	2	0.354	9.0	87
39550315	3	0.382	9.7	101
39550415	4	0.429	10.9	128
39550515	5	0.457	11.6	155
▶ 14 AWG (≈ 46/30) • 2.50 mm²				
39550225	2	0.409	10.4	128
39550325	3	0.449	11.4	148
39550425	4	0.512	13.0	188
39550525	5	0.563	14.3	228
▶ 12 AWG (≈ 52/28) • 4.00 mm²				
39550240	2	0.476	12.1	161
39550340	3	0.511	13.0	205
39550440	4	0.567	14.4	262
39550540	5	0.634	16.1	316

item no.	no. of conductors incl. ground	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
▶ 10 AWG (≈ 78/28) • 6.00 mm²				
39550160	1	0.323	8.2	94
39550260	2	0.539	13.7	195
39550360	3	0.575	14.6	333
39550460	4	0.650	16.5	349
39550560	5	0.713	18.1	430
▶ 8 AWG (≈ 77/26) • 10.00 mm²				
39550161	1	0.394	10.0	141
39550261	2	0.748	19.0	356
39550361	3	0.803	20.4	591
39550461	4	0.858	21.8	638
39550561	5	0.965	24.5	773
▶ 6 AWG (≈ 122/26) • 16.00 mm²				
39550162	1	0.441	11.2	195
39550262	2	0.843	21.4	491
39550362	3	0.902	22.9	847
39550462	4	0.965	24.5	941
39550562	5	1.075	27.3	1142
▶ 4 AWG (≈ 190/26) • 25.00 mm²				
39550163	1	0.508	12.9	276
39550263	2	1.012	25.7	665
39550363	3	1.079	27.4	979
39550463	4	1.197	30.4	1310
39550563	5	1.283	32.6	1613

item no.	no. of conductors incl. ground	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
▶ 2 AWG (≈ 272/26) • 35.00 mm²				
39550164	1	0.579	14.7	376
39550364	3	1.193	30.3	1282
39550464	4	1.323	33.6	1814
▶ 1 AWG (≈ 400/26) • 50.00 mm²				
39550165	1	0.677	17.2	497
39550365	3	1.386	35.2	1734
39550465	4	1.535	39.0	2419
▶ 2/0 AWG (≈ 543/26) • 70.00 mm²				
39550166	1	0.752	19.1	706
39550366	3	1.555	39.5	2305
39550466	4	1.728	43.9	2980
▶ 3/0 AWG (≈ 484/24) • 95.00 mm²				
39550167	1	0.850	21.6	874
39550367	3	1.772	45.0	2957
39550467	4	1.984	50.4	4166
▶ 4/0 AWG (≈ 589/24) • 120.00 mm²				
39550168	1	0.933	23.7	1048
▶ 250 MCM (≈ 740/24) • 150.00 mm²				
39550169	1	1.028	26.1	1335
▶ 350 MCM (≈ 902/24) • 185.00 mm²				
39550170	1	1.130	28.7	1546
▶ 450 MCM (≈ 1220/24) • 240.00 mm²				
39550171	1	1.256	31.9	2083
▶ 550 MCM (≈ 1525/24) • 300.00 mm²				
39550172	1	1.370	34.8	2345

Other dimensions and colors are possible on request.