



2

d	Tolerances		h	Tolerances		Nominal magnetic forces in N		
	HF	SC / ND		HF	SC / ND	HF Hard ferrite	SC SmCo	ND NdFeB
6	-	±0,1	4,5	-	±0,1	-	5	5
8	-	±0,1	4,5	-	±0,1	-	11	13
10	±0,1	±0,1	4,5	+0,2/-0,1	±0,1	4	20	25
13	±0,1	±0,1	4,5	+0,2/-0,1	±0,1	10	40	60
16	±0,1	±0,1	4,5	+0,2/-0,1	±0,1	18	60	95
20	±0,1	±0,1	6	+0,2/-0,1	±0,1	30	90	140
25	±0,1	±0,1	7	+0,3/-0,1	±0,2	40	150	200
32	±0,1	±0,1	7	+0,3/-0,1	±0,2	80	220	350
40	+0,2/-0,1	-	8	+0,4/-0,1	-	125	-	-
50	+0,2/-0,1	-	10	+0,5/-0,1	-	220	-	-
63	+0,3/-0,1	-	14	+0,5/-0,1	-	350	-	-
80	+0,5/-0,1	-	18	+0,5/-0,1	-	600	-	-
100	+0,5/-0,1	-	22	+0,5/-0,1	-	900	-	-
125	+0,5/-0,1	-	26	+0,5/-0,1	-	1300	-	-

## Specification

- Housing  
Steel, zinc plated
- Materials of the magnet:
  - Hard ferrite  
temperature resistant up to 200 °C
  - SmCo  
Samarium, cobalt  
temperature resistant up to 200 °C
  - NdFeB  
Neodymium, iron, boron  
temperature resistant up to 80 °C

• RoHS

1

## Information

Retaining magnets GN 50.1 are a shielded magnetic system.

Fixed in place by gluing or side-mounted thrust bolt (e.g. GN 913.2 grub screw with pointed nose).

see also...

- *More information to retaining magnets → Page 1380 ff.*
- *Holding discs GN 70 → Page 1414*

How to order

GN 50.1-SC-13

1 Material of the magnet

2 d