



NOTES

1. MATERIAL: PHOSPHOR BRONZE
 THICKNESS : 0.30 * 0.02
 WIDTH : 22.8 * 0.08
2. PLATING: PREPLATING (REFLOW TREATMENT)
3. MALE TAB (THICK 0.6 ± 0.05 +) FIT.
 - INSERTION FORCE: 0.8Kgf. MAX.
 - RETENTION FORCE: 0.3Kgf. MIN.
4. WIRE SIZE : AWG #18±#22 35028-9010

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC:				molex	
mm		6:1							
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 628958		.070 FEMALE TERMINAL			
				DRWN: VRAMAKANTALA 2019/09/09				DOCUMENT NUMBER	
4 PLACES ±				CHK'D: GGA 2020/01/16		SD-35028-XXXX		PSD	001
3 PLACES ±				APPR: GGA 2020/01/16		PRODUCT CUSTOMER DRAWING			J
2 PLACES ± 0.15				INITIAL REVISION:		MATERIAL NUMBER		CUSTOMER	
1 PLACE ± 0.15				DRWN: H.J.KIM 1994/06/25		35028		GENERAL MARKET	
0 PLACES ±				APPR: YSKIM02 2013/01/04		SEE TABLE		1 OF 1	
ANGULAR TOL ± 0.5°				THIRD ANGLE PROJECTION		DRAWING		SHEET NUMBER	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				A3-SIZE		SERIES			