

View on mating side

o	A	A	A	A	A	A	A	A	A	A	A	A	A
o													
o	A	A	A	A	A	A	A	A	A	A	A	A	A

1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0

A = 32 standard contacts L=2

Marking	Standard
Performance level	G2/0 = Contact area perform. level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	609-6043-201 sht.1
Technical Data	PS-85013-0002

A	G2/0	d1-l6	cl-l6
Contact symbol	Perform. level	Contact position number	

ECN No. MG1999-0303	REVISIONS				REVISE ONLY ON CAD SYSTEM			SH.	REV.
	FOR PREVIOUS REVISIONS SEE MRL LIST				CAD/CAM PROJECT NAME	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
first release	INCH	UNLESS OTHERWISE SPECIFIED, TOLERANCES: ANGULAR ±2°		DRWG BY	SIGN				
	METRIC	3 PLACE ±	±	Cd					
	3 PLACE ±	±		CHK'D BY	SIGN				
	2 PLACE ±	±		Er					
	1 PLACE ±	±		APP'D BY	SIGN				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				FB					
DESIGN DIMENSION	<input checked="checked" type="checkbox"/> MM	<input type="checkbox"/> IN.	SCALE						
EQUIVALENT DIMENSION	<input type="checkbox"/> MM	<input type="checkbox"/> IN.							
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY									
LTR	TITLE				MOLEX EUROPE		SHEET NO.	DATE	SIZE
A	48 pos. Male connector acc. DIN 41612 style R/2 contacts arrangement				1 OF 1		99/05/27	85013-0062	A
	PART NO.				DWG NO.		SDA-85013-0062		