



PushPull



Han® PushPull, type acc. to IEC 61 076-3-117 variant 14 SCRJ connector

## Features

- HARTING PushPull technology
- Compact design
- High packing density
- Han® PushPull SCRJ for POF is according the requirements of AIDA (German Domestic Automobile Manufacturers)
- Field installable

## Technical characteristics

Locking	PushPull technology
Degree of protection	IP65 / IP67
Mating face	SCRJ acc. to IEC 61 754-24
Fiber Typen	POF <sup>1)</sup> 1 mm HCS <sup>2)</sup> 200 µm / 230 µm MM 62.5 µm / 125 µm MM 50 µm / 125 µm SM 10 µm / 125 µm
Mating cycles	min. 750
Temperature range	-40 °C ... +70 °C
Housing material	Plastic, black
Flammability acc. to UL 94	V0
Cable diameter	6.5 - 9.5 mm

Identification	Part number	Drawing	Dimensions in mm
<b>Connector set, plastic</b> incl. housing and SCRJ insert, POF contacts  PROFINET-Identification: PROFINET O-Plug SCRJ  incl. housing and SCRJ insert SC contacts order separately	09 35 241 0421  09 35 241 0422		
<b>SCRJ IP20 POF connector</b>	09 35 002 4002		
<b>Protection cover IP65 / IP67</b>	09 35 002 5411		
<b>Contacts</b>  SC POF contact, 1 mm SC 125 GI contact SC 230 HCS contact	20 10 001 5217 20 10 125 5211 20 10 230 5211		