


M12 Ultra-Lock Shielded

RJ45S


Electrical Data:
 Ultra-Lock Shielded to RJ45S cordset
 According to CAT5e Ethernet Standard.
 Poles: 8
 Max. Voltage: 30V
 Max Current: 1,5A
 Contact resistance: <5m Ohm
 Insulation withstand: >100M Ohm
 Protection Ultra-Lock: IP67
 Temperature range: -25°C to 60°C

Male



1. White/Blue
2. White/Brown
3. Brown
4. Orange
5. White/Green
6. White/Orange
7. Blue
8. Green

Male



12345678

1. White/Orange
2. Orange
3. White/Green
4. Blue
5. White/Blue
6. Green
7. White/Brown
8. Brown

SAP Nr.	L (mm)
1201080001	3.000
1201085005	1.000
1201085024	500
1201085049	10.000

Customer Drawing
 Kundenzeichnung

This drawing and its contents are the proprietary and confidential property of Woodhead Industries Inc. and/or its subsidiaries and may not be used or disclosed to others without the express prior written consent of Woodhead Industries Inc. and/or its subsidiaries.					
		UNLESS OTHERWISE SPECIFIED x = ±1 X.X = ±0,1 X.XX = ±0,05 Winkel = 1°	Scale 2:1	Dimensions mm	
PROJECTION 1 : GER			Material Finish		
		Date	Name	Ethernet Cordset M12US - RJ45S	
		PROC 14.04.2008	US		
		CHK 11.11.2008	NS		
		Norm. 22.01.2010	FP		
05	10M variant added	20.01.10	NS	Woodhead Connectivity GmbH	
04	WEU2009-0147	11.11.08	US	SPR 4913	
03	WEU2009-0049	07.08.08	US	Gwerbestraße 60	
02	Update	15.04.08	US	75015 Bretten-Gölshausen	
01	INITIAL RELEASE	14.04.08	US	Tel.: 07252/9496-0	
Rev.	Change	Date	Name	Fax: 07252/9496-199	
				SD-120108-001	
				Sheet 1	
				A3	
				Filename SD-120108-001.idw	