

PHBC10-0R8A0038V Aliases (UALP100R8A0038)

D т 1.5max 9.0±3.0 S

General Information Series PHBC Style Through-Hole Switching Power Suppy Outlet, DC-DC Converter, Phase Compensation, Noise Solution Features RoHS Yes Miscellaneous 15 (K) Temperature Rise Max. Core Fe-Ni

Specifications	
Inductance	38 uH (0.1 MHz)
Inductance Tolerance	20%
Current	3 A
Temperature Range	-40/+125°C
DC Resistance	31.2 mOhms

Click here for the 3D model.

Dimensions	
D	21.5mm MAX
т	11.7mm MAX
LL	9mm +/-3mm
S	8mm NOM
Wire Size	0.8mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	240
Component Weight	11 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET, PHBC, AC Line Filters, Normal Mode, 0.038 mH, 20%