

Programmable Single Channel DC Power Supply

MPS-3600H Series



- Nine sets of voltage and current storage and recall function, convenient and quick
- Output switch control, easy control
- Input voltage 110V/220V switching, universal
- Intelligent temperature control fan, extremely practical
- The knob adopts the code switch, which is convenient to use and has the function of preventing misadjustment
- LIST programme output function
- Set current and voltage regulation range
- Save last time output data and state
- External trigger function
- Pass/fail signal output function
- Standard with RS-232, SENSE, analog control is optional

Application:

1. Routine test and maintenance of production line;
2. Laboratory and Research Institute;
3. Simulation test of new energy vehicles;
4. Automation equipment integration test

Standard RS-232 SENSE

Optional Analog control

Model		MPS-3603H	MPS-3605H	MPS-3610H	MPS-6003H	MPS-6005H	MPS-8002H
Rated output voltage		0~36V	0~36V	0~36V	0~60V	0~60V	0~80V
Rated output current		0~3A	0~5A	0~10A	0~3A	0~5A	0~2A
Rated output power		108W	180W	360W	180W	300W	160W
Load regulation rate	Voltage	0.05%+5mV	0.05%+8mV	0.05%+10mV	0.05%+5mV	0.05%+8mV	0.05%+5mV
	Current	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
Line regulation	Voltage	0.05%+5mV	0.05%+8mV	0.05%+10mV	0.05%+5mV	0.05%+8mV	0.05%+5mV
	Current	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
Setting value resolution	Voltage	1mV	1mV	1mV	1mV	1mV	1mV
	Current	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA
Readback value resolution	Voltage	1mV	1mV	1mV	1mV	1mV	1mV
	Current	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA
Setting accuracy (25°C±5°C)	Voltage	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+3digits
	Current	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+6digits	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+3digits
Readback accuracy (25°C±5°C)	Voltage	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+3digits
	Current	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+6digits	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+3digits
Ripple	Voltage	1mVrms	1.5mVrms	2mVrms	2mVrms	2mVrms	3mVrms
	Current	3mArms	3mArms	6mArms	3mArms	3mArms	3mArms
Temperature Coefficient	Operation	300ppm	300ppm	300ppm	300ppm	300ppm	300ppm
	Storage	300ppm	300ppm	300ppm	300ppm	300ppm	300ppm
Instrument size (W*H*D)	mm	215*95*300	215*95*300	215*95*355	215*95*355	215*95*355	215*95*300
Packing size (W*H*D)	mm	310*200*420	310*200*420	310*200*485	310*200*485	310*200*485	310*200*420
Net weight	kg	4.5	6.7	7.5	5.6	7	5.6
Gross weight	kg	5.6	7.8	8.6	6.7	8	6.7