

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0334722063](#)  
**Status:** **Active**  
**Overview:** [MX150 Sealed and Unsealed Connector System](#)  
**Description:** [MX150 Mat-Sealed Female Connector Assembly, Dual Row, 20 Circuits, Keying Option D, with Connector Position Assurance, Stone Gray](#)

**Documents:**

|   |  |
|---|--|
| <a href="#">3D Model (PDF)</a>                                      | <a href="#">Application Specification AS-33611-001-001 (PDF)</a> |
| <a href="#">3D Model</a>  | <a href="#">Packaging Specification PK-31300-903-001 (PDF)</a>   |
| <a href="#">Drawing (PDF)</a>                                       | <a href="#">Test Summary TS-33472-0001-001 (PDF)</a>             |
| <a href="#">Product Specification PS-33472-000-001 (PDF)</a>        | <a href="#">Datasheet (PDF)</a>                                  |
| <a href="#">Application Specification AS-33472-100-001 (PDF)</a>    | <a href="#">RoHS Certificate of Compliance (PDF)</a>             |
| <a href="#">Application Specification AS-33472-100-CH-001 (PDF)</a> |  |

**General**

|                |  |
|----------------|--|
| Product Family | Crimp Housings   |
| Series         | <a href="#">33472</a>                                      |
| Application    | Power, Wire-to-Board, Wire-to-Wire                         |
| Comments       | with Connector Position Assurance (CPA)                    |
| Overview       | <a href="#">MX150 Sealed and Unsealed Connector System</a> |
| Product Name   | MX150  |
| UPC            | 884982301993   |

**Physical**

|                               |                    |
|-------------------------------|--------------------|
| Circuits (maximum)            | 20                 |
| Color - Resin                 | Stone Gray         |
| Gender                        | Receptacle         |
| Glow-Wire Capable             | No                 |
| Keying to Mating Part         | Yes                |
| Lock to Mating Part           | Yes                |
| Material - Resin              | SPS/Nylon          |
| Net Weight                    | 21.875/g           |
| Number of Rows                | 2                  |
| Packaging Type                | Partitioned Carton |
| Panel Mount                   | No                 |
| Pitch - Mating Interface      | 3.50mm             |
| Polarized to Mating Part      | Yes                |
| Stackable                     | No                 |
| Temperature Range - Operating | -40° to +150°C     |

**Solder Process Data**

|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

**Material Info**

**Reference - Drawing Numbers**

|                           |   |
|---------------------------|---|
| Application Specification | AS-33472-100-001, AS-33472-100-CH-001, AS-33611-001-001 |
| Packaging Specification   | PK-31300-903-001  |
| Product Specification     | PS-33472-000-001  |
| Sales Drawing             | 334722002-001, SD-33472-0001-001, SD-33472-0002-002     |
| Test Summary              | TS-33472-0001-001                                       |



Series image - Reference only

**EU ELV**

**Compliant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per - D(2020)9139-DC (19 Jan 2021)

**Halogen-Free**

**Status**

**Not Relevant**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Not Relevant

Compliant

Not Contained

**Search Parts in this Series**

[33472 Series](#)

**Mates With**

MX150 Male Sealed Connector [33483](#)

**Use With**

MX150 Female Terminal [33012](#) , [33001](#) <br>MX150 Sealed Cavity PlugLink:343450001

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**