

Specification Sheet

Part Number: 173-00800



Electromagnetic Protection Braided Sleeving, 8 mm Dia, PET;TNCU, TCBK, 328ft/Reel

Article Number	173-00800
Туре	HEGEMIP08
Color	Tin-coloured and Black (TCBK)
Features & Benefits	Unique blend of polyester and tin plated copper fibers offers electromagnetic protection as well as secure cable bundling
Quantity Per	metre

Product Description

Made of tin-plated copper and polyester threads, Helagaine HEGEMIP braided sleeving offers electromagnetic protection as well as secure cable bundling. The patented material mix offers very good inside and outside abrasion resistance. Also it makes the sleeve expandable and easy to apply. In contrast to purely copper braids, the HEGEMIP sleeve can be bent and twisted and still return to their original form to protect the cable perfectly. The copper wires are protected by the polyester yarn. Therefore breaks and fractures of the metal are prevented, even by bending the sleeve at a 90°-angle. As a result, HEGEMIP braided sleeving is particularly suitable for applications where there is movement and restricted space The inner tube makes insertion of cables easier and protects the sleeves from deformation during transportation.

Short Description	Electromagnetic Protection Braided Sleeving, 8 mm Dia, PET;TNCU, TCBK, 328ft/Reel
Global Part Name	HEGEMIPO8-PET/SNCLI-MI

Length L (Imperial)	328.0
Length L (Metric)	100.0
Bundle Diameter Min (Imperial)	0.32
Bundle Diameter Min (Metric)	8
Bundle Diameter Max (Imperial)	0.45
Bundle Diameter Max (Metric)	11
Diameter D (imperial)	0.31
Diameter D (metric)	8
Nominal Diameter (Imperial)	5/16

Nominal Diameter (Metric)

Material	Tin-plated copper (SNCU) Polyester, halogen free (PET)
Material Shortcut	PET SNCU
Flammability	UL 94 V2 FMVSS 302
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	328
Package Quantity (Metric)	100
Customs Number	5808100000
Content Unit(BMEcat)	metre
Weight (Metric)	2.6
Weight (Imperial)	5.84

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions