


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

Item No.	Part No.	Description	TABLE 1				
1	See Table 1	XSR Connector	ITEM	NUMBER OF CIRCUITS	CONNECTOR PART NO.	ASSEMBLY PART NO.	TOTAL WIRE REQUIRED
2	UL11136, 36 AWG	Red	1	2	02XSR-36S	A02XSR02XSR36R102A	212 mm
			1	4	04XSR-36S	A04XSR04XSR36R102A	424 mm
			1	6	06XSR-36S	A06XSR06XSR36R102A	637 mm
			1	10	10XSR-36S	A10XSR10XSR36R102A	1061 mm
			1	16	16XSR-36S	A16XSR16XSR36R102A	1698 mm
			1	20	20XSR-36S	A20XSR20XSR36R102A	2122 mm
			1	22	22XSR-36S	A22XSR22XSR36R102A	2334 mm

<u>Electrical Specifications</u>
Current: 0.2A AC/DC
Voltage: 30V AC/DC



All dimensions are in millimeters with a default tolerance of +/- 5.0 unless otherwise specified.		CUSTOMER NAME		
		DESCRIPTION		
		0.6mm Pitch XSR Standard Catalog Assembly - 4" Overall Length - Pin Out: 1 to 1		
Drawn By: Larissa Mosley	SIZE	CUSTOMER PART NO.	PART NO.	REV
Checked By: Steven Pilkington	SCALE	SEE TABLE 1		
	2:1	DRAWING NO. GAM-273	DATE 4/05/2018	

ZONE	REV	DESCRIPTION	DATE	APPROVED
	1	Add Electrical Specifications	7/03/2018	LM