


- UFBK 2-PE/L- 48DC-BE - 2792170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Base element UFBK 2-PE/L for protective plug UFBK 2-PE/L 48 V DC, with universal foot for mounting on NS 32 or NS 35/7.5, nominal voltage: 48 V DC

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 118501
Weight per Piece (excluding packing)	68.42 GRM
Custom tariff number	85363010
Country of origin	Germany

Technical data

Dimensions

Horizontal pitch	1 Div.
------------------	--------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Degree of protection	IP20

General

Stripping length	8 mm
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG/kcmil max.	14
Nominal current I _N	2 A
Housing material	PA
Inflammability class according to UL 94	V2
Pollution degree	2

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801

- UFBK 2-PE/L- 48DC-BE - 2792170

Classifications

eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130803

ETIM

ETIM 2.0	EC000472
ETIM 3.0	EC000472
ETIM 4.0	EC000472

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 13.2	39121620