

RM4A(03)-220X185

Aliases (UFSRM4030BT000)

KEMET, RM4A, Flex Suppressors, RFID

No Drawing Available.
Click [here](#) for the 3D model.

Dimensions

Sheet Size 220x185mm
L 220mm NOM
W 185mm NOM
T 0.3mm NOM

Packaging Specifications

Tape Description No Adhesive Tape
Component Weight 43.96 g

General Information

Series RM4A
Style Sheet
Description Flex Suppressor Magnetic Sheet For RFID
Features High Magnetic Permeability Type, Low Magnetic Loss Type
RoHS Yes
Environment Halogen Free, PVC Free, Lead Free, RoHS Compliant

Specifications

Temperature Range -40/+85°C
Permeability 50 u At 13.56MHz
Effective Frequency 13.56 MHz and below
Specific Gravity 3.6 TYP
Surface Resistivity 10 MOhm/sq. TYP

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - e70d879a-1d03-4a7d-8196-3a6ee96ecc51
© 2006 - 2023 KEMET
Generated 5/18/2023 - e70d879a-1d03-4a7d-8196-3a6ee96ecc51
© 2006 - 2023 KEMET