



## Main

|                           |  |
|---------------------------|--|
| Range of Product          | Harmony XVR                                      |
| Product or Component Type | Prewired rotating mirror beacon                  |
| Sound signalling          | Without  |
| Device short name         | XVR  |
| Mounting diameter         | 3.31 in (84 mm)                                  |
| IP degree of protection   | IP65 IEC 60529 with accessory)<br>IP23 IEC 60529 |
| [Us] rated supply voltage | 24 V AC/DC                                       |
| Light source              | High luminosity LED, green                       |

## Complementary

|  |   |
|--|---|
| Material                               | ABS (acrylonitrile butadiene-styrene) body part<br>PC globe |
| CAD overall width                      | 3.31 in (84 mm)   |
| CAD overall depth                      | 3.31 in (84 mm)   |
| Net Weight                             | 0.66 lb(US) (0.3 kg)  |
| Marking                                | CE  |
| Product mounting                       | By 3 M4 screws  |
| Supply voltage limits                  | 19...30 V DC<br>21.6...26.4 V AC                            |
| [Uimp] rated impulse withstand voltage | 0.8 kV  |
| Current Consumption                    | 125 mA  |
| Flashing frequency                     | 2.3 Hz  |
| Clamping connection capacity           | 0.83 mm <sup>2</sup>  |
| AWG gauge                              | AWG 18  |
| Cable length                           | 19.69 in (500 mm)   |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Standards                             | EN 61000-6-4<br>EN 61000-6-2 |
| Product Certifications                | UL                           |
| Protective treatment                  | TC                           |
| Ambient Air Temperature for Storage   | -31...158 °F (-35...70 °C)   |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C)    |
| Electrical shock protection class     | Class II IEC 61140           |

## Ordering and shipping details

|                       |                          |
|-----------------------|--------------------------|
| Category              | 22617 - XVC TOWER LIGHTS |
| Discount Schedule     | XV                       |
| GTIN                  | 3606480033018            |
| Nbr. of units in pkg. | 1                        |
| Package weight(Lbs)   | 13.76 oz (390 g)         |
| Returnability         | No                       |
| Country of origin     | ID                       |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 7.48 in (19 cm)         |
| Package 1 width              | 3.86 in (9.8 cm)        |
| Package 1 Length             | 3.94 in (10 cm)         |
| Unit Type of Package 2       | S03                     |
| Number of Units in Package 2 | 6                       |
| Package 2 Weight             | 6.73 lb(US) (3.053 kg)  |
| Package 2 Height             | 11.81 in (30 cm)        |
| Package 2 width              | 11.81 in (30 cm)        |
| Package 2 Length             | 15.75 in (40 cm)        |
| Unit Type of Package 3       | PAL                     |
| Number of Units in Package 3 | 48                      |
| Package 3 Weight             | 41.27 lb(US) (18.72 kg) |
| Package 3 Height             | 23.62 in (60 cm)        |
| Package 3 width              | 31.50 in (80 cm)        |
| Package 3 Length             | 18.90 in (48 cm)        |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |



## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Rotating Mirror Beacon

Dimensions

mm  
in.



---

Rotating Mirror Beacon

---

Panel Cut-out

