



RESISTANCE VS TEMPERATURE CHARACTERISTICS:

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	291.2	304.4	318.1	50	3.49	3.561	3.634
-35	213.6	222.6	231.9	55	2.879	2.944	3.01
-30	158.3	164.4	170.8	60	2.388	2.446	2.505
-25	118.4	122.6	127	65	1.989	2.041	2.095
-20	89.39	92.32	95.34	70	1.664	1.711	1.759
-15	68.17	70.21	72.31	75	1.399	1.44	1.483
-10	52.38	53.81	55.27	80	1.18	1.217	1.256
-5	40.53	41.53	42.55	85	1.001	1.034	1.069
0	31.58	32.27	32.98	90	0.853	0.882	0.913
5	24.72	25.2	25.69	95	0.729	0.756	0.783
10	19.48	19.82	20.15	100	0.625	0.649	0.674
15	15.46	15.68	15.91	105	0.539	0.56	0.582
20	12.33	12.49	12.64	110	0.465	0.484	0.504
25	9.9	10	10.1	115	0.403	0.42	0.438
30	7.955	8.053	8.151	120	0.351	0.366	0.382
35	6.427	6.52	6.613	125	0.306	0.32	0.334
40	5.218	5.304	5.392	130	0.261	0.274	0.286
45	4.257	4.337	4.417	135	0.216	0.228	0.238

NOTES:

1. RESISTANCE @ 25°C : 10KΩ±1%.
2. BETA VALUE (0/50°C) : 3892K±1%
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR : 1.5mW/°C
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE : 10MΩ AT 100 VDC

FUNCTIONAL SYMBOLS ▽/A = 0 ▽/E = 0 ▽/V = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	SCALE mm NTS	CURRENT REV DESC:		molex
	GENERAL TOLERANCES (UNLESS SPECIFIED)	ANGULAR TOL ± °	EC NO: 657230 DRWN: RAVIKM CHK'D: RBBHASKAR APPR: RBBHASKAR		
DIVISIONAL SYMBOLS	4 PLACES ±	3 PLACES ±	2021/03/03	2021/03/05	PRODUCT CUSTOMER DRAWING
	2 PLACES ±	1 PLACE ±	2021/03/05	2021/03/05	
	0 PLACES ±	INITIAL REVISION: DRWN: RAVIKM APPR: RBBHASKAR	2021/03/03	2021/03/05	DOC TYPE PSD
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING A3-SIZE	SERIES 215272	DOC PART 000
			MATERIAL NUMBER 2152723605	CUSTOMER OTS	REVISION A
					SHEET NUMBER 1 OF 1