



USB-C to USB-A Adapter (M/F), Right-Angle C, USB 3.2 Gen 1 (5 Gbps), Thunderbolt 3 Compatible, 6-in. (15.24 cm)

MODEL NUMBER: U428-06N-F-CRA











USB Type-C to Type-A adapter connects an existing USB cable or device to your MacBook or Chromebook's USB-C or Thunderbolt 3 port.

Features

USB Type-C to USB Type-A Adapter Connects an Existing USB Device to Your USB-C LaptopThis six-inch USB Type-C to Type-A adapter allows you to connect USB devices to your smartphone, tablet, laptop, MacBook, Chromebook or Ultrabook's USB-C or Thunderbolt 3 port. USB wall chargers, hard drives, memory sticks, printers and other peripherals with USB-A ports will be able to communicate with your computer or other USB-C mobile device.

PD Charging Cable Charges Devices and Transfers Data at Fast USB 3.1 Gen 1 SpeedsThe USB-C to USB-A adapter supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps, which is 10 times faster than USB 2.0. The Power Delivery cable also provides power output up to 3 amps (60 watts), which is more than sufficient for charging, syncing and powering compatible devices. The cable is backward compatible with previous USB generations, allowing you to use it with older USB 3.0, USB 2.0 or USB 1.1 equipment.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Right-Angle USB-C Plug Makes Connecting in Tight Spaces EasierThe space-saving right-angle USB-C plug is easy to install in confined spaces, such as behind your computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

Highlights

- Right-angle USB-C plug permits easier connection in confined or hard-to-reach spaces
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Power Delivery cable provides 3A (60W) power output for charging mobile devices
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-C to USB-A cable compatible with all USB-A, USB-C and Thunderbolt 3 devices

Applications

- Charge and sync a USB-C or Thunderbolt 3 mobile device from a USB-A wall charger
- Connect a printer or scanner to a desktop computer's hard-toreach rear USB-C port
- Transfer data between an external hard drive or flash drive and your computer or laptop

System Requirements

- Device with a USB-C or Thunderbolt 3 port (USB 3.1 Gen 1 compatibility required to achieve USB 3.1 Gen 1 speeds)
- · Device with a USB-A port

Package Includes

 U428-06N-F-CRA Right-Angle USB Type-C to Type-A Adapter Cable, M/F, 6 in.

Specifications

| OVERVIEW | |
|----------------|--------------|
| UPC Code | 037332214133 |
| USB Cable Type | Passive |





| PHYSICAL | | |
|---------------------------------|-------------------------------------|--|
| Material of Construction | PVC | |
| Cable Jacket Color | Black | |
| Cable Jacket Rating | VW-1 | |
| Cable Outer Diameter (OD) | 4.5 mm | |
| Cable Length (ft.) | 0.5 | |
| Cable Length (m) | 0.15 | |
| Cable Length (in.) | 6 | |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 22.86 x 17.78 x 1.27 | |
| Shipping Weight (lbs.) | 0.04 | |
| Shipping Weight (kg) | 0.02 | |
| Unit Packaging Type | Polybag | |
| ENN/IDONINENTAL | | |
| ENVIRONMENTAL | 201, 440 5 (0.1, 45.0) | |
| Operating Temperature Range | 32 to 113 F (0 to 45 C) | |
| Storage Temperature Range | 14 to 158 F (-10 to 70 C) | |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing | |
| Storage Humidity Range | 5% to 90% RH, Non-Condensing | |
| CONNECTIONS | | |
| Side A - Connector 1 | USB C (MALE) - RIGHT ANGLE | |
| Side B - Connector 1 | USB 3.0 A (FEMALE) | |
| Connector Plating | Nickel | |
| Contact Plating | Gold | |
| FEATURES & ORFOLEIOATIONS | | |
| FEATURES & SPECIFICATIONS | 110D 0.4.0 co.4.(m.); 5.0(m.) | |
| USB Specification | USB 3.1 Gen 1 (up to 5 Gbps) | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period | | |
| (Worldwide) | Lifetime limited warranty | |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies