

Specification Sheet

Part Number: 156-02723

One-piece ratchet closure allows for easy installation during pre- or final assembly.

Easy release feature simplifies quick adjustments and maintenance.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

3M™ VHB™ adhesive on base creates an incredible bond with mounting surface.



Adhesive Mount Ratchet Clamp, 0.50 - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/bag

Article Number 156-02723

Type IRCBMB5A

Color Black (BK)

Quantity Per bag

Product Description

The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fittings and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

| | |
|-------------------------------------|---|
| Short Description | Adhesive Mount Ratchet Clamp, 0.50 - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/bag |
| Global Part Name | IRCBMB5A-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 100.0 |
| Minimum Tensile Strength (Metric) | 445.0 |
| Length L (Imperial) | 1.37 |
| Length L (Metric) | 34.8 |
| Fixation Method | Adhesive |
| Width W (Imperial) | 1.37 |
| Width W (Metric) | 34.9 |
| Bundle Diameter Min (Imperial) | 0.50 |
| Bundle Diameter Min (Metric) | 12.70 |
| Bundle Diameter Max (Imperial) | 0.77 |
| Bundle Diameter Max (Metric) | 19.56 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |

| | |
|------------------------------|-----------------------------------|
| Material Shortcut | PA66HIRHSUV |
| Adhesive | Acrylic |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 25 |
| Package Quantity (Metric) | 25 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)