

## Data sheet | Item number: 211-501

Shrink tube; for Smart Printer; Unshrunk diameter: 3.2 mm; white

[www.wago.com/211-501](http://www.wago.com/211-501)



### Data

#### Technical data

|                             |   |
|-----------------------------|---|
| Suitable                    | for wire cross-section 0.75 ... 1 mm <sup>2</sup> |
| Marking method              | Thermal transfer                                  |
| Delivery form               | Roll  |
| Delivery form configuration | 20 m/roll   |
| Printing device             | Smart Printer (Thermal Transfer Printer)          |

#### Physical data

|                         |          |
|-------------------------|----------|
| Depth                   | 0.185 mm |
| Sheathed cable diameter | 3.2 mm   |

#### Mechanical Data

|               |                      |
|---------------|----------------------|
| Mounting type | Sliding on conductor |
| Shrink rate   | 2:1                  |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

Smear resistance

in conjunction with 258-5005 Ink Ribbon

## Material Data

|                      |                               |
|----------------------|-------------------------------|
| Color                | white                         |
| Material             | Polyolefin                    |
| UV resistance        | EN 60068-2-5:2010 Procedure B |
| Adhesive information | without adhesive              |
| Halogen-free         | Yes                           |
| Weight               | 180.5 g                       |

## Environmental requirements

|                                 |                 |
|---------------------------------|-----------------|
| Ambient temperature (storage)   | +10 ... +25 °C  |
| Ambient temperature (operation) | -55 ... +125 °C |
| Relative humidity               | 45 ... 55 %     |

## Commercial data

|                       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-40-04-01   |
| eCl@ss 9.0            | 27-40-04-01   |
| ETIM 8.0              | EC001530      |
| ETIM 7.0              | EC001530      |
| PU (SPU)              | 1 pcs         |
| Packaging type        | box           |
| Country of origin     | DK            |
| GTIN                  | 4055143370226 |
| Customs tariff number | 39173200910   |

## Environmental Product Compliance

|                        |                         |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

## Optional accessories

### Marking accessories

|                 |
|-----------------|
| Marking devices |
|-----------------|



Item no.: 258-5000

Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material

[www.wago.com/258-5000](http://www.wago.com/258-5000)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



## Downloads

### Documentation

#### Operating Instructions

---

|  |             |        |          |
|--|-------------|--------|----------|
| 211-502 Information on printing material | 1           | pdf    | Download |
|  | 2020 Aug 28 | 1.1 MB |          |

---

## Environmental Product Compliance

### Compliance Search

---

|  |     |          |
|--|-----|----------|
| Environmental Product Compliance 211-501                         | URL | Download |
| Shrink tube; for Smart Printer; Unshrunk diameter: 3.2 mm; white |     |          |

---

## Installation Notes

Subject to changes. Please also observe the further product documentation!