



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂ Thread	Length l ≈ GN 6335.4							Length l ≈ GN 6335.4					d ₄	h ₁	h ₂
		16	20	25	30	35	45	-	20	25	30	40	-			
32 1.26	M 6	.63	.79	.98	1.18	1.38	1.77	-	-	-	-	-	12 .47	20 .79	9 .35	
40 1.57	M 8	.59	.79	.98	1.18	1.57	2.17	.79	.98	1.18	1.57	-	14 .55	25 .98	13 .51	
50 1.97	M 10	.98	1.18	1.38	1.77	2.17	-	.79	.98	1.18	1.77	2.17	18 .71	32 1.26	18 .71	
63 2.48	M 12	1.18	1.38	1.57	1.97	2.36	-	1.18	1.57	1.97	-	-	20 .79	40 1.57	23 .91	
80 3.15	M 16	1.18	1.57	1.97	2.36	2.76	-	-	-	-	-	-	25 .98	50 1.97	28 1.10	

Specification

- GN 6335.4**
 - Threaded stud
Steel, blackened finish
 - Hand knob
Cast iron, fettled and tumbled **SG**
- GN 6335.5**
 - Threaded stud
Stainless steel
European Standard No. 1.4305 (AISI 303)
 - Hand knob
Stainless steel precision casting **ES**
European Standard No. 1.4308 (AISI CF-8)
Matte shot-blasted finish
 - Hand knob
Aluminum, forged **AM**
Matte, tumbled finish **AP**
Polished finish **AP**
- For all types the threaded stud is screwed in and secured by a cross-dowel pin.
- RoHS compliant

On request

- Special inch and metric stud lengths

Information

GN 6335.4 cast iron hand knobs extend the range of clamping applications and are perfect for medium to heavy duty clamping applications. GN 6335.5 hand knobs have very good corrosion resistant properties.

see also...

- Hand Knobs GN 6335.4 (Plastic, with Steel Threaded Stud)
- Hand Knobs GN 6335.5 (Plastic, with Stainless Steel Threaded Stud)
- Star Knobs GN 5334 / GN 5334.4 (Stainless Steel)
- Wing Screws GN 433 (Stainless Steel)
- Wing Screws GN 835 (Stainless Steel)

How to order (Steel threaded stud)	1 Material
 GN 6335.4-SG-50-M10-35	2 Handle diameter d₁
	3 Thread d₂
	4 Length l

How to order (Stainless steel threaded stud)	1 Finish (Material)
 GN 6335.5-AP-40-M8-20	2 Handle diameter d₁
	3 Thread d₂
	4 Length l