

**SS** Stainless Steel

**4 Type (Base)**

- D0** Without rubber pad / cap
- B0** Without rubber pad / cap, with 2 mounting holes
- D1** With rubber cap, clipped on, black
- D3** With rubber pad, vulcanized, black







**Inch table (only available in version S, SK, U, UK, X)**

Dimensions in: inches - millimeters

d <sub>1</sub>	d <sub>2</sub> Thread	l <sub>1</sub>				l <sub>7</sub>				d <sub>3</sub>	m	h <sub>1</sub>	h <sub>6</sub>	s	
		Version S / SK				Version U / UK									Version X
1.57 40	5/16 x 18	-	-	-	-	-	-	-	-	0.98 25	0.21 5.4	1.18 30	0.08 2	0.14 3.5	0.06 1.5
1.57 40	3/8 x 16	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.10 28	0.21 5.4	1.18 30	0.08 2	0.14 3.5	0.06 1.5
1.57 40	1/2 x 13	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.22 31	0.21 5.4	1.18 30	0.08 2	0.14 3.5	0.06 1.5
1.57* 40	5/8 x 11	-	-	-	-	2.95 75	3.94 100	4.92 125	5.91 150	1.46 37	0.21 5.4	1.18 30	0.08 2	0.14 3.5	0.06 1.5
1.97 50	5/16 x 18	-	-	-	-	-	-	-	-	0.98 25	0.26 6.6	1.50 38	0.10 2.5	0.16 4	0.08 2
1.97 50	3/8 x 16	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.10 28	0.26 6.6	1.50 38	0.10 2.5	0.16 4	0.08 2
1.97 50	1/2 x 13	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.26 32	0.26 6.6	1.50 38	0.10 2.5	0.16 4	0.08 2
1.97 50	5/8 x 11	-	-	-	-	2.95 75	3.94 100	4.92 125	5.91 150	1.46 37	0.26 6.6	1.50 38	0.10 2.5	0.16 4	0.08 2
2.36 60	5/16 x 18	-	-	-	-	-	-	-	-	0.98 25	0.26 6.6	1.89 48	0.10 2.5	0.18 4.5	0.08 2
2.36 60	3/8 x 16	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.10 28	0.26 6.6	1.89 48	0.10 2.5	0.18 4.5	0.08 2
2.36 60	1/2 x 13	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.26 32	0.26 6.6	1.89 48	0.10 2.5	0.18 4.5	0.08 2
2.36 60	5/8 x 11	-	-	-	-	2.95 75	3.94 100	4.92 125	5.91 150	1.46 37	0.26 6.6	1.89 48	0.10 2.5	0.18 4.5	0.08 2
3.15 80	5/16 x 18	-	-	-	-	-	-	-	-	1.02 26	0.33 8.5	2.52 64	0.12 3	0.20 5	0.08 2
3.15 80	3/8 x 16	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.14 29	0.33 8.5	2.52 64	0.12 3	0.20 5	0.08 2
3.15 80	1/2 x 13	2.95 75	3.94 100	4.92 125	5.91 150	-	-	-	-	1.26 32	0.33 8.5	2.52 64	0.12 3	0.20 5	0.08 2
3.15 80	5/8 x 11	-	-	-	-	2.95 75	3.94 100	4.92 125	5.91 150	1.50 38	0.33 8.5	2.52 64	0.12 3	0.20 5	0.08 2
3.15 80	3/4 x 10	-	-	-	-	3.94 100	4.92 125	5.91 150	-	1.77 45	0.33 8.5	2.52 64	0.12 3	0.20 5	0.08 2

\* Not available in type B0

d <sub>1</sub>	d <sub>2</sub> Thread	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	A/F <sub>1</sub>	A/F <sub>2</sub>	A/F <sub>3</sub>	A/F <sub>7</sub>	t
1.57 40	5/16 x 18	-	-	-	-	-	-	0.55 14	0.31 8
1.57 40	3/8 x 16	0.43 11	-	-	0.67 17	-	-	0.55 14	0.39 10
1.57 40	1/2 x 13	0.43 11	-	-	0.67 17	-	-	0.67 17	0.47 12
1.57 40	5/8 x 11	-	0.67 17	0.55 14	-	0.47 12	0.31 8	0.87 22	0.63 16
1.97 50	5/16 x 18	-	-	-	-	-	-	0.55 14	0.31 8
1.97 50	3/8 x 16	0.43 11	-	-	0.67 17	-	-	0.55 14	0.39 10
1.97 50	1/2 x 13	0.43 11	-	-	0.67 17	-	-	0.67 17	0.47 12
1.97 50	5/8 x 11	-	0.67 17	0.55 14	-	0.47 12	0.31 8	0.87 22	0.63 16
2.36 60	5/16 x 18	-	-	-	-	-	-	0.55 14	0.31 8
2.36 60	3/8 x 16	0.43 11	-	-	0.67 17	-	-	0.55 14	0.39 10
2.36 60	1/2 x 13	0.43 11	-	-	0.67 17	-	-	0.67 17	0.47 12
2.36 60	5/8 x 11	-	0.67 17	0.55 14	-	0.47 12	0.31 8	0.87 22	0.63 16
3.15 80	5/16 x 18	-	-	-	-	-	-	0.55 14	0.31 8
3.15 80	3/8 x 16	0.47 12	-	-	0.67 17	-	-	0.55 14	0.39 10
3.15 80	1/2 x 13	0.47 12	-	-	0.67 17	-	-	0.67 17	0.47 12
3.15 80	5/8 x 11	-	0.71 18	0.59 15	-	0.47 12	0.31 8	0.87 22	0.63 16
3.15 80	3/4 x 10	-	0.75 19	0.59 15	-	0.59 15	0.39 10	1.06 27	0.79 20

Stud / socket versions		
 <p><b>5</b> <b>S</b> Without nut <b>SK</b> With nut</p>	 <p><b>5</b> <b>T**</b> Without nut <b>TK**</b> With nut</p>	 <p><b>5</b> <b>U</b> Without nut <b>UK</b> With nut</p>
External hexagon at the bottom at d <sub>2</sub> 3/8 x 16, 1/2 x 13 M 8, M 10, M 12	Wrench flat at the bottom at d <sub>2</sub> - M 16, M 20, M 24	Internal hexagon at the top, wrench flat at the bottom at d <sub>2</sub> 5/8 x 11, 3/4 x 10 M 16, M 20, M 24
 <p><b>5</b> <b>V**</b> Without nut <b>VK**</b> With nut</p>	 <p><b>5</b> <b>W**</b> With adjustable sleeve</p>	 <p><b>5</b> <b>X</b> Tapped socket type</p>
External hexagon at the top, wrench flat at the bottom at d <sub>2</sub> - M 16, M 20, M 24	Covered thread, wrench flat at the bottom at d <sub>2</sub> - M 16, M 20, M 24	External hexagon with tapped socket at d <sub>2</sub> 5/16 x 18, 3/8 x 16, 1/2 x 13, 5/8 x 11, 3/4 x 10 M 8, M 10, M 12, M 16, M 20

\*\* Only available with Metric thread

3.1  
3.2  
3.3  
3.4  
3.5  
3.6  
3.7  
3.8  
3.9  
3.10



**Metric table**

Dimensions in: millimeters - inches

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub>	<sup>3</sup> l <sub>1</sub>										<sup>3</sup> l <sub>2</sub>				<sup>3</sup> l <sub>3</sub>				<sup>3</sup> l <sub>7</sub>	
Thread	Version S / SK	Version T / TK and U / UK				Version V / VK					Version W				Version X						
40 1.57	M 8	40 1.57	50 1.97	63 2.48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25 0.98
40 1.57	M 10	50 1.97	60 2.36	80 3.15	100 3.94	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	28 1.10
40 1.57	M 12	60 2.36	80 3.15	100 3.94	125 4.92	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	31 1.22
40* 1.57	M 16	-	-	-	-	75 2.95	100 3.94	125 4.92	150 5.91	200 7.87	-	-	-	-	-	-	-	-	-	-	37 1.46
50 1.97	M 8	40 1.57	50 1.97	63 2.48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25 0.98
50 1.97	M 10	50 1.97	60 2.36	80 3.15	100 3.94	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	28 1.10
50 1.97	M 12	60 2.36	80 3.15	100 3.94	125 4.92	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	32 1.26
50 1.97	M 16	-	-	-	-	75 2.95	100 3.94	125 4.92	150 5.91	200 7.87	-	-	-	-	-	-	-	-	-	-	37 1.46
60 2.36	M 8	40 1.57	50 1.97	63 2.48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25 0.98
60 2.36	M 10	50 1.97	60 2.36	80 3.15	100 3.94	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	28 1.10
60 2.36	M 12	60 2.36	80 3.15	100 3.94	125 4.92	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	32 1.26
60 2.36	M 16	-	-	-	-	75 2.95	100 3.94	125 4.92	150 5.91	200 7.87	75 2.95	100 3.94	125 4.92	150 5.91	110 4.33	135 5.31	160 6.30	185 7.28	-	-	37 1.46
80 3.15	M 8	40 1.57	50 1.97	63 2.48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	26 1.02
80 3.15	M 10	50 1.97	60 2.36	80 3.15	100 3.94	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	29 1.14
80 3.15	M 12	60 2.36	80 3.15	100 3.94	125 4.92	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	32 1.26
80 3.15	M 16	-	-	-	-	75 2.95	100 3.94	125 4.92	150 5.91	200 7.87	75 2.95	100 3.94	125 4.92	150 5.91	110 4.33	135 5.31	160 6.30	185 7.28	-	-	38 1.50
80 3.15	M 20	-	-	-	-	75 2.95	100 3.94	125 4.92	150 5.91	200 7.87	100 3.94	125 4.92	150 5.91	200 7.87	134 5.28	159 6.26	184 7.24	234 9.21	45 1.77	-	-
80 3.15	M 24	-	-	-	-	100 3.94	125 4.92	150 5.91	200 7.87	-	100 3.94	150 5.91	200 7.87	-	159 6.26	209 8.23	259 10.20	-	-	-	-

\* Not available in type B0

d <sub>1</sub>	d <sub>2</sub> Thread	d <sub>3</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	h <sub>6</sub>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>	A/F <sub>1</sub>	A/F <sub>2</sub>	A/F <sub>3</sub>	A/F <sub>4</sub>	A/F <sub>5</sub>	A/F <sub>6</sub>	A/F <sub>7</sub>	m	s	t
40 1.57	M 8	5.4 0.21	-	2 0.08	11 0.43	-	-	3.5 0.14	-	-	-	17 0.67	-	-	-	-	-	14 0.55	30 1.18	1.5 0.06	8 0.31
40 1.57	M 10	5.4 0.21	-	2 0.08	11 0.43	-	-	3.5 0.14	-	-	-	17 0.67	-	-	-	-	-	14 0.55	30 1.18	1.5 0.06	10 0.39
40 1.57	M 12	5.4 0.21	-	2 0.08	11 0.43	-	-	3.5 0.14	-	-	-	17 0.67	-	-	-	-	-	17 0.67	30 1.18	1.5 0.06	12 0.47
40 1.57	M 16	5.4 0.21	-	2 0.08	-	17 0.67	14 0.55	3.5 0.14	-	-	-	-	12 0.47	8 0.31	-	-	-	22 0.87	30 1.18	1.5 0.06	16 0.63
50 1.97	M 8	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4 0.16	-	-	-	17 0.67	-	-	-	-	-	14 0.55	38 1.50	2 0.08	8 0.31
50 1.97	M 10	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4 0.16	-	-	-	17 0.67	-	-	-	-	-	14 0.55	38 1.50	2 0.08	10 0.39
50 1.97	M 12	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4 0.16	-	-	-	17 0.67	-	-	-	-	-	17 0.67	38 1.50	2 0.08	12 0.47
50 1.97	M 16	6.6 0.26	-	2.5 0.10	-	17 0.67	14 0.55	4 0.16	-	-	-	-	12 0.47	8 0.31	-	-	-	22 0.87	38 1.50	2 0.08	16 0.63
60 2.36	M 8	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4.5 0.18	-	-	-	17 0.67	-	-	-	-	-	14 0.55	48 1.89	2 0.08	8 0.31
60 2.36	M 10	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4.5 0.18	-	-	-	17 0.67	-	-	-	-	-	14 0.55	48 1.89	2 0.08	10 0.39
60 2.36	M 12	6.6 0.26	-	2.5 0.10	11 0.43	-	-	4.5 0.18	-	-	-	17 0.67	-	-	-	-	-	17 0.67	48 1.89	2 0.08	12 0.47
60 2.36	M 16	6.6 0.26	24 0.94	2.5 0.10	-	17 0.67	14 0.55	4.5 0.18	45 1.77	45 1.77	29 1.14	-	12 0.47	8 0.31	10 0.39	12 0.47	20 0.79	22 0.87	48 1.89	2 0.08	16 0.63
80 3.15	M 8	8.5 0.33	-	3 0.12	12 0.47	-	-	5 0.20	-	-	-	17 0.67	-	-	-	-	-	14 0.55	64 2.52	2 0.08	8 0.31
80 3.15	M 10	8.5 0.33	-	3 0.12	12 0.47	-	-	5 0.20	-	-	-	17 0.67	-	-	-	-	-	14 0.55	64 2.52	2 0.08	10 0.39
80 3.15	M 12	8.5 0.33	-	3 0.12	12 0.47	-	-	5 0.20	-	-	-	17 0.67	-	-	-	-	-	17 0.67	64 2.52	2 0.08	12 0.47
80 3.15	M 16	8.5 0.33	24 0.94	3 0.12	-	18 0.71	15 0.59	5 0.20	45 1.77	45 1.77	29 1.14	-	12 0.47	8 0.31	10 0.39	12 0.47	20 0.79	22 0.87	64 2.52	2 0.08	16 0.63
80 3.15	M 20	8.5 0.33	30 1.18	3 0.12	-	19 0.75	15 0.59	5 0.20	56 2.20	56 2.20	37 1.46	-	15 0.59	10 0.39	13 0.51	16 0.63	24 0.94	27 1.06	64 2.52	2 0.08	20 0.79
80 3.15	M 24	8.5 0.33	35 1.38	3 0.12	-	22 0.87	18 0.71	5 0.20	67 2.64	67 2.64	42 1.65	-	19 0.75	12 0.47	17 0.67	20 0.79	30 1.18	-	64 2.52	2 0.08	-

**Specification**

- Base  
Stainless steel, plain, tumbled finish  
European Standard No. 1.4301 (AISI 304)
- Threaded stud / tapped socket  
Stainless steel  
European Standard No. 1.4305 (AISI 303)
- Hexagon nut ISO 4032  
Stainless steel  
European Standard No. 1.4301 (AISI 304)
- Rubber cap  
Santoprene® (TPE) ≈ 80 shore A  
- Clipped on  
- Black
- Rubber pad  
Perbunan® (NBR) 70 ±5 shore A  
- Vulcanized, non-skid  
- Black
- RoHS compliant

**On request**

- Stud versions T / TK, V / VK and W with Inch thread with certain minimum quantities


**Information**


GN 41 leveling feet are intended for use in aggressive environments. The wide range of possible combinations of the base and the adjusting spindle variants make these leveling feet universally applicable. The base with the rubber pad / cap protects sensitive surfaces and reduces lateral slippage. The type B0 can also be fastened to the mounting surface through two holes.

These leveling feet are supplied fully assembled and cannot be disassembled.

see also...

- Leveling Feet GN 40 (Steel, without Fixing Lug)
- Leveling Feet GN 42 (Steel, with Fixing Lug)
- Leveling Feet GN 42 (Steel, with Slotted Lag Bolt Hole, Rectangular Shape)
- Leveling Feet GN 43 (Stainless Steel AISI 304, with Fixing Lug)
- Leveling Feet GN 44 / GN 45 (Stainless Steel AISI 316, with / without Fixing Lug)
- Threaded Tube Ends EN 448 (Plastic)
- Threaded Tube Inserts GN 992 / GN 992.5 (Aluminum / Stainless Steel)

<p>How to order (Inch)</p>  <p><b>GN 41-40-5/16X18-25-B0-X</b></p>	1	Base diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
	3	Length l <sub>7</sub> (Length l <sub>1</sub> )
	4	Type (Base)
	5	Stud / socket version

<p>How to order (Metric)</p>  <p><b>GN 41-80-M16-75-D0-TK</b></p>	1	Base diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
	3	Length l <sub>1</sub> (Length l <sub>2</sub> , l <sub>3</sub> , l <sub>7</sub> )
	4	Type (Base)
	5	Stud / socket version

3.1  
3.2  
3.3  
3.4  
3.5  
3.6  
3.7  
3.8  
3.9  
3.10

