

Specification Sheet

Part Number: 151-00837



Designed for use with MBTS(-S), MBTH(-S), and MBTSFC stainless steel ties, or 18 through 120 pound nylon cable ties to provide stability when securing bundles.

Secures with a single screw providing quick installation.

Stainless Steel Tie Mount, 0.16" Hole Dia, 0.39" Max Tie Width, Grade 316 SST, ML, 100/pkg

Article Number 151-00837

Type SSPC4

Color Metal (ML)

Quantity Per bag

Product Description

Stainless steel P-mounts provide a robust and extremely durable fixing solution for a wide range of applications. With a 10mm slot width and either a 4mm, 5mm or 6mm fixing hole, this '2-way' mount can be installed quickly and easily with a single screw or bolt providing excellent performance and a high pull force. Designed for heavy duty applications and made out of a high grade stainless steel 316 material, these P-mounts provide resistant to chemicals, salt spray, extreme weather conditions and corrosion. They are also non-flammable, ensuring a highly secure and safe fixing solution.

Short Description	Stainless Steel Tie Mount, 0.16" Hole Dia, 0.39" Max Tie Width, Grade 316 SST, ML, 100/pkg
Global Part Name	SSPC4-SS316-ML
Length L (Imperial)	0.91
Length L (Metric)	23.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.40
Width W (Metric)	10.2
Cable Ties	MBTS(-S) and MBTH(-S) stainless steel ties
Height H (Imperial)	0.18
Height H (Metric)	4.5
Cable Tie Width Max (Imperial)	0.39
Cable Tie Width Max (Metric)	10.0
Mounting Hole Diameter D (Imperial)	0.16
Mounting Hole Diameter D (Metric)	4.2 mm
Mounting Hole Diameter D Max (Metric)	4.2

Material	Stainless Steel (SS316)
Material Shortcut	SS316
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	7326908695

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)