

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fully mounted relay modules with spring-cage connection, consisting of: relay base, plug-in industrial relay with integrated LED, free-wheeling diode and engage/disengage manual actuate lever, and relay retaining bracket. Input voltage: 24 V DC, 2 PDT, 10 A

Your advantages

- Relay with detectable manual operation and status LED
- With DC types, freewheeling diode is integrated in relay
- Logical contact arrangement thanks to 1/3-level relay base
- 4 PDT types with multi-layer gold contacts
- Mechanical switch position indicator



Key Commercial Data

Packing unit	5 pc
GTIN	 4 046356 044547
GTIN	4046356044547

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	31 mm
Height	95 mm
Depth	84 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Coil side

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685

Technical data

Coil side

Nominal input voltage U_N	24 V DC
Typical input current at U_N	38 mA
Typical response time	13 ms
Typical release time	5 ms
Protective circuit	Damping diode
Operating voltage display	Green LED
Power dissipation for nominal condition	0.91 W

Contact side

Contact type	2 PDT
Type of switch contact	Single contact
Contact material	Ag
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V
Min. switching current	1 mA
Maximum inrush current	20 A (15 ms)
Limiting continuous current	10 A
Interrupting rating (ohmic load) max.	240 W (at 24 V DC)
	144 W (at 48 V DC)
	108 W (at 60 V DC)
	72 W (at 110 V DC)
	110 W (at 220 V DC)
	2500 VA (for 250 V AC)

General

Test voltage relay winding/relay contact	2 kV (50 Hz, 1 min.)
Test voltage relay contact/relay contact	2 kV (50 Hz, 1 min.)
Operating mode	100% operating factor
Mechanical service life	5×10^7 cycles
Service life, electrical	see diagram
Mounting position	any
Assembly instructions	In rows with zero spacing

Connection data input side

Connection name	Coil side
Connection method	Spring-cage connection
Stripping length	12 mm
Conductor cross section solid	0.2 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16

Standards and Regulations

Standards/regulations	IEC 60664
-----------------------	-----------

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685

Technical data

Standards and Regulations



	EN 50178
Pollution degree	3
Overvoltage category	II

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings


Circuit diagram



DC coils

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685


Diagram



Operating voltage range of relay $T_u=T_{coil}$

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685


Diagram



AC interrupting rating

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685


Diagram



DC interrupting rating

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685

Diagram



- ① 250 V AC, ohmic load
- ② 30 V DC, ohmic load

Electrical service life

Articles in set

Relay base - PR2-BSP3/4X21 - 2833589



Relay base PR2-B, for industrial relay REL-IR with 2 or 4 PDT, 1/3-level version, spring-cage connections, connection facility for input/interference suppression modules, for mounting on NS 35/7.5

Single relay - REL-IR/LDP- 24DC/2X21 - 2834025



Pluggable industrial relays with power contacts, 2 PDT, test button, status LED, free-wheeling diode, mechanical switch position indicator, polarity A1+, A2-, input voltage 24 V DC

Relay Module - PR2-RSP3-LDP-24DC/2X21 - 2834685

Articles in set

Retaining bracket - EL2-P35 - 2833592



Relay retaining bracket, with eject function and integrated equipment marking area (8 x 25 mm), to suit relay base PR2, for 35 mm high industrial relay

Approvals

Approvals


Approvals

EAC / EAC

Ex Approvals

Approval details

EAC		TR_TS_D_00573_c
-----	---	-----------------

EAC		TR_TS_S_00010_c
-----	---	-----------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>