



△ DIMENSION

Dim A	Nx7.5
Dim B	Nx7.5+1.40

N=Number of poles

Poles	Tolerance
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	10/17/13	Add is cULus ////add the view	Da cheng

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material**
- Item (a) Terminal (Body): Thermoplastic (UL94V-0)
 - Item (b) Terminal (Lever): Thermoplastic (UL94V-0)
 - Item (c) Spring clamp : Stainless Steel
 - Item (d) Female Contact : PhBz(CuSn), Tin plated
 - Item (e) Terminal (Cover): Thermoplastic (UL94V-0)

- △ Electrical** cULus
- Voltage rating: 300VAC
 - Current rating: 10A
 - Solid wire(AWG): 14-26
 - Stranded wire(AWG): 14-26
 - Wire strip length: 7-8mm
 - Withstanding Voltage: 1.6KV
 - Size of the PCB: 1.6±0.2mm
 - Operating temperature: -40°C to +115°C
- △ Safety Approval:**
- Critical dimension:

ND xx A0 x 0 xxxx G △ RoHs compliant (lead<4%) In copper Alloy

- △ No. of poles**
- 02 2 poles
 - 03 3 poles
 -
 - 16 16 poles
- △ Color**
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7004/P)
 - 9 White(RAL1102)
 - C Multiple colors
- 0000:"@”Logo (Standard)
000A:"ANYTEK”Logo
Any special item by customer request, please contact sales department.

ANYTEK		CUSTOMER COPY		ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
				TITLE ND 7.5 Series		PART NO. NDxxA0x0xxxxG	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Dacheng 2013.10.21	Dacheng 2013.10.21			X. ±0.5	
						UNIT: mm	
						SCALE: NONE	
SHEET: 01/01				REV.: C		X.XX ±0.1	
						X° ±1°	