



- △ COUPLING RING: POLYPHENYLENE, BLACK.
 ADAPTER, HOUSING AND PRESSURE PLATE: NYLON, BLACK.
 WIRE ENTRY SEAL: ELASTOMER, RED-IRON OXIDE.
- 2. CONNECTOR WILL ACCEPT (37) MULTIMATE SOCKET CONTACTS.
- △ 3. ORIENTATION HOLE USED IN THE MANUFACTURING PROCESS ONLY.
 THIS HOLE IS NOT INTENDED FOR WIRE INSERTION.

796288-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C. DORWART 11 NOV 98		TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
		0. PLC ± -	1. PLC ± -	NAME: PLUG ASSEMBLY, SIZE 23-37, STANDARD SEX, SERIES I, SEALED CIRCULAR PLASTIC CONNECTOR	
		2. PLC ± ± 0.13(.005)	3. PLC ± ± -	PRODUCT SPEC: 108-1579	
		4. PLC ± ± -	ANGLES ± ± -	APPLICATION SPEC: -	
MATERIAL: △ 1		FINISH: -		SIZE: A1	CAGE CODE: 00779
		WEIGHT: -		DRAWING NO: 796288	
		CUSTOMER DRAWING		SCALE: 2:1	SHEET 1 OF 1