



Click [here](#) for the 3D model.

### Dimensions

D	36.6mm +/-1mm
L	51.5mm +/-1mm
T	4.4mm NOM
S	13mm +/-0.5mm
F	8mm +/-0.5mm
DT	8mm NOM
LT	58.9mm +/-1mm

### Packaging Specifications

Sleeving	Yes
Packaging	Bulk, Bag
Packaging Quantity	42

### General Information

Series	PEH169
Dielectric	Aluminum Electrolytic
Description	Screw Terminal, Aluminum Electrolytic
RoHS	Yes
Mounting	Stud
AEC-Q200	No
Halogen Free	Yes
Component Weight	70 g
Notes	Dimensions D And L Include Sleeving. M5. MS = M8x12.
Shelf Life	156 Weeks

### Specifications

Capacitance	2,200 uF
Capacitance Tolerance	20%
Voltage DC	63 VDC
Temperature Range	-40/+85°C
Rated Temperature	85°C
Life	14000 Hrs (Rated Voltage And Ripple Current At 85C)
Resistance	46 mOhms (100Hz 20C), 24 mOhms (100kHz 20C)
Ripple Current	5.9 Amps (100Hz 85C), 25.1 Amps (10kHz 50C), 17.1 Amps (10kHz 40C)
Leakage Current	4415.8 uA (5min 20°C)
Inductance	12 nH (ESL)