VIEW ON MATING SIDE

	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
c	C	X	C	C	C	X	C	C	C	C	C	C	C	C	C	C
b	B	Y	B	B	B	B	B	B	B	B	B	B	B	B	Y	B
a	A	Z	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A = 15 STANDARD CONTACTS L= 3.0
B = 14 STANDARD CONTACTS L= 3.0
C = 14 STANDARD CONTACTS L= 3.0
Z = 1 FMLB CONTACTS +0.6 L= 3.0
Y = 2 FMLB CONTACTS +0.6 L= 3.0
X = 2 FMLB CONTACTS +0.6 L= 3.0

S = 48 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0002 SHT 1

CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER
X	G2/0	c11, 15
Y	G2/0	b2, 15
Z	G2/0	a15
C	G2/0	c1-10, 12-14, 16
B	G2/0	b1, 3-14, 16
A	G2/0	a1-14, 16

B 1 2004-XXXX
N.S 09/09/03
G.L 09/09/03
G.L 09/09/03

S.S	20/04/01	48 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C/2 CONTACTS ARRANGEMENT
G.L	20/04/01	
G.L	20/04/01	

SD-85003-2737.S0185003-2737 SD-85003-2737 1 OF 1

NO.

SIZE D