



SurgeGate™ Modular Metal Housing



Features:

- Agency Approval UL Primary (497) and Isolated Loop (497B)
- Exceeds TIA/EIA Standards 568 and 758 for CAT 6 performance
- Solid-state protection provides the fastest response to transient voltages (1-5 nanoseconds) by quickly diverting damaging surges to ground
- Use between buildings in a campus environment as a building entrance protector or in hostile industrial applications as an isolated loop protector
- RJ45 input to RJ45 output
- Suggested Applications Include: Security cameras, POE, Phone systems, Ethernet, & VOIP
- Available in 75V clamping voltage.



TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

| | |
|---------------------------------|--|
| Agency Approval | UL Primary (497) and Isolated Loop (497B) |
| Ground Requirements | Field installed solid copper wire #6 AWG for Primary #14 AWG for Isolated Loop |
| Recommended Grounding Impedance | <0.5 Ohm |
| Height / Width / Depth | 1.0" / 2.75" / 3.75" |
| Weight w/o Modules | N/A |
| Product Warranty | 5 Years |
| Connected Equipment Warranty | Up to \$5,000 |

SINGLE LINE SURGE PROTECTION: (LAN)

| | |
|--------------------------|---------------------------|
| Signal Perfect Circuitry | Yes |
| Fused | No |
| Performance Rating | CAT6 (Gigabit) |
| Clamping Level | CAT6-75-MM = 75V |
| Response Time | 1-5 Nanoseconds |
| Capacitance | <20pF |
| Wires Protected | 8-wires, 4-pairs per port |
| Termination Type | RJ-45 In & Out |