

## Specification Sheet

Part Number: 133-02353



Bundling clip with gradual transition provides security to bundles around panel edges.

Flanged ends prevent slip in tape wrap.

4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

<b>Article Number</b>	133-02353
<b>Type</b>	FTOVALSTRNRLF
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	carton
<b>Product Description</b>	Designed for use with cable ties or electrical tape, bundling clips provide a simple method of securing wire and cable bundles. HellermannTyton offers these clips in standard and standoff orientations, with a variety of mounting options.
<b>Short Description</b>	Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn
<b>Global Part Name</b>	FTOVALSTRNRLF-PA66HIRHSUV-BK

<b>Length L (Imperial)</b>	2.55
<b>Length L (Metric)</b>	64.7
<b>Fixation Method</b>	Fir Tree
<b>Height H (Imperial)</b>	0.89
<b>Height H (Metric)</b>	22.6
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.27
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.26" x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB

<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	4000
<b>Package Quantity (Metric)</b>	4000
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)