



SS Stainless Steel

**Inch table**

Dimensions in: inches - millimeters

| <sup>1</sup> d <sub>1</sub> | <sup>2</sup> d <sub>2</sub> Thread | <sup>3</sup> Length l |           |            | d <sub>3</sub> | b         | h <sub>1</sub> | h <sub>2</sub> | t min.    |
|-----------------------------|------------------------------------|-----------------------|-----------|------------|----------------|-----------|----------------|----------------|-----------|
| 1.02<br>26                  | 10 x 32                            | .39<br>10             | .63<br>16 | -          | .39<br>10      | .43<br>11 | .39<br>10      | .18<br>4.5     | .31<br>8  |
| 1.02<br>26                  | 1/4 x 20                           | .63<br>16             | .79<br>20 | .98<br>25  | .39<br>10      | .43<br>11 | .39<br>10      | .18<br>4.5     | .31<br>8  |
| 1.34<br>34                  | 1/4 x 20                           | .79<br>20             | .98<br>25 | 1.18<br>30 | .47<br>12      | .51<br>13 | .47<br>12      | .20<br>5       | .39<br>10 |
| 1.34<br>34                  | 5/16 x 18                          | .63<br>16             | .79<br>20 | 1.18<br>30 | .47<br>12      | .51<br>13 | .47<br>12      | .20<br>5       | .39<br>10 |

**Metric table**

Dimensions in: millimeters - inches

| <sup>1</sup> d <sub>1</sub> | <sup>2</sup> d <sub>2</sub> Thread | <sup>3</sup> Length l |           |            | d <sub>3</sub> | b         | h <sub>1</sub> | h <sub>2</sub> | t min.    |
|-----------------------------|------------------------------------|-----------------------|-----------|------------|----------------|-----------|----------------|----------------|-----------|
| 26<br>1.02                  | M 4                                | -                     | -         | -          | 10<br>.39      | 11<br>.43 | 10<br>.39      | 4.5<br>.18     | 7<br>.28  |
| 26<br>1.02                  | M 5                                | 10<br>.39             | 16<br>.63 | -          | 10<br>.39      | 11<br>.43 | 10<br>.39      | 4.5<br>.18     | 8<br>.31  |
| 26<br>1.02                  | M 6                                | 16<br>.63             | 20<br>.79 | 25<br>.98  | 10<br>.39      | 11<br>.43 | 10<br>.39      | 4.5<br>.18     | 8<br>.31  |
| 34<br>1.34                  | M 6                                | 20<br>.79             | 25<br>.98 | 30<br>1.18 | 12<br>.47      | 13<br>.51 | 12<br>.47      | 5<br>.20       | 10<br>.39 |
| 34<br>1.34                  | M 8                                | 16<br>.63             | 20<br>.79 | 30<br>1.18 | 12<br>.47      | 13<br>.51 | 12<br>.47      | 5<br>.20       | 9<br>.35  |

**Specification**

- Stainless steel precision casting  
European Standard No. 1.4308 (AISI CF-8)  
Matte shot-blasted finish

MT

- RoHS compliant

**Information**

Where a greater torque is required GN 434 wing nuts and GN 433 wing screws are a better solution than knurled nuts.

see also...

- Wing Nuts GN 834 (Stainless Steel)
- Wing Screws GN 835 (Stainless Steel)
- Hand Knobs DIN 6335 (Stainless Steel)

|   |   |
|---|---|
| How to order (Inch wing nut)                                  | <sup>1</sup> Handle diameter d <sub>1</sub> |
| <sup>1</sup> <sup>2</sup> <sup>4</sup><br>GN 434-34-1/4X20-MT | <sup>2</sup> Thread d <sub>2</sub>          |
|   | <sup>4</sup> Finish                         |

|   |   |
|---|---|
| How to order (Metric wing screw)  | <sup>1</sup> Handle diameter d <sub>1</sub> |
| <sup>1</sup> <sup>2</sup> <sup>3</sup> <sup>4</sup><br>GN 433-26-M6-16-MT | <sup>2</sup> Thread d <sub>2</sub>          |
|   | <sup>3</sup> Length l                       |
|   | <sup>4</sup> Finish                         |