



LOC	DIST	REV	DATE	APPD
G	14			

METPRIO
DIMENSIONS LISTED IN mm [INCHES]

REVISIONS	DESCRIPTION	DATE	APPD
1	REVISED PER 0720-0230-93		

AMP WIRE RANGE	UL E13288 Listed
12-10 AWG STRANDED	12-10 AWG STRANDED
LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 12-10* APPROX AS SHOWN

AMP INCORPORATED
CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS
1-800-522-6752

FOR APPLICATION TOOLS INFORMATION CENTER
1-800-722-1111

FOR ORDER ENTRY
1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE: 170°C MAX

VOLTAGE RATING: NOT APPLICABLE

WIRE CROSS SECTIONAL AREA RANGE: 2.62-6.64mm² [5.180-13.100] CIR MILS STRANDED

FINISH: TIN PLATE
0.00254L.0001001 MIN THK PER MIL-T-10727

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN - - - - - THICKNESS - - - - - TOLERANCES ON 1 2 PLG DEC ± 3 PLG DEC ± ANGLES MATERIAL	DR 2-9-93 TA BRINKMAN	CHK 2-9-93 DA PATTERSON	APPD 2-9-93 DE MILLER	APPD 2-9-93 J. HECKLEY	PRODUCT SPEC
APPROXIMATE WEIGHT	APPLICATION SPEC	SCALE 10:1	SIZE CAGE CODE	DRAWING NO	
			00779	G-32882	

AMP Incorporated
Harrisburg, PA 17105-3508

TERMINAL, RING TONGUE, BUDGET

32882 PART NO

CUSTOMER DRAWING 1 OF 1