



PCB LAYOUT

**MATERIALS AND FINISHES**

SSMCX JACKS:  
 BODY: BRASS  
 PLATED: GOLD OVER NICKEL  
 CONTACT: BERYLLIUM COPPER  
 PLATED: GOLD OVER NICKEL  
 INSULATOR: TEFLON

SOLDER POSTS: BRASS  
 PLATED: TIN

BLOCKS:  
 HIGH TEMP NYLON

73358-0320	GANG 4 STANDARD WITH POSTS
PART NO.	DESCRIPTION

<b>CHG: RELEASE DRAWING.</b> EC NO: URF2010-0124 DRAWN: ROBERTSON 2009/08/26 CHKD: SSS 2009/08/26 APPR: JWIENER 2009/08/26 REV: A	<b>QUALITY SYMBOLS</b> ▽=0 ▽=0	<b>GENERAL TOLERANCES (UNLESS SPECIFIED)</b>		<b>DIMENSION STYLE</b> MM/IN	<b>SCALE</b> METRIC	<b>DESIGN UNITS</b> METRIC	<b>THIRD ANGLE PROJECTION</b>																
		<table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>3 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>2 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>1 PLACE</td> <td>± .005</td> <td>± .0005</td> </tr> </table>			mm	INCH	4 PLACES	± .005	± .0005	3 PLACES	± .005	± .0005	2 PLACES	± .005	± .0005	1 PLACE	± .005	± .0005	DRAWN BY: AZR DATE: 2009/08/21	<b>TITLE</b> SSMCX J 4 PORT STANDARD PCB SMT 50 OHMS W/POSTS EWR-4158 SSMCX-J/PCB			
			mm	INCH																			
		4 PLACES	± .005	± .0005																			
3 PLACES	± .005	± .0005																					
2 PLACES	± .005	± .0005																					
1 PLACE	± .005	± .0005																					
APPROVED BY: JDW DATE: 2009/08/21		<b>MOLEX INCORPORATED</b>																					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		<b>SEE TABLE</b>		<b>DOCUMENT NO.</b> SD-73358-032		<b>SHEET NO.</b> 1 OF 1																	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION