

Specification Sheet

Part Number: 181-00172



Solid Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 30ft/box

Article Number

181-00172

Type

SD1X2

Color

Gray (GY)

Features & Benefits

- Solid wall construction provides excellent coverage to keep wires clean.
- Durable material protects wires from damage, with long-lasting performance.
- Available standard colors complement or contrast in light and dark environments.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

Quantity Per

box

Product Description

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.

| | |
|---|--|
| Short Description | Solid Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 30ft/box |
| Global Part Name | SD1X2-PVC-GY |
| Technical Description | Non-Adhesive |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 1.0 |
| Width W (Metric) | 25.4 |
| Height H (Imperial) | 2.07 |
| Height H (Metric) | 52.6 |
| Mounting Hole Centers (Imperial) | 4.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Certification/Specification WEB

CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 UL

UL Recognized (US)

Yes

Package Quantity(Imperial)

30

Package Quantity (Metric)

9.14

Customs Number

3925900000