

# EMMY-W1 series




## Host-based multiradio modules with Wi-Fi and Bluetooth

### The most robust and comprehensive modules with Wi-Fi and Bluetooth® coexistence

- Automotive and professional grades
- Dual-band Wi-Fi with IEEE 802.11ac
- Dual-mode Bluetooth v4.2 with BR/EDR and Bluetooth low energy
- Simultaneous client and micro access point operation for up to 10 clients
- Integrated LTE filter



13.8 × 19.8 × 2.5 mm



### Product description

EMMY-W1 is an ultra-compact multiradio module providing Wi-Fi 802.11ac, Bluetooth BR/EDR, and Bluetooth low energy with an extended temperature range from -40 °C to +85 °C offered in automotive and professional grades. It is designed for both simultaneous and independent operations of:

- Wi-Fi IEEE 802.11ac and a/b/g/n
- Dual-mode Bluetooth v4.2

EMMY-W1 is an SMD component that can easily be integrated into the application. Together with a host and the free-of-charge driver, it provides a complete wireless modem solution. The module is connected to the host processor through SDIO and High-Speed UART interfaces. EMMY-W1 is radio type approved for Europe, US, Canada, Japan, South Korea, Taiwan, China, and Australia/New Zealand.

### Key features

- Wi-Fi Standards IEEE 802.11a/b/g/n/ac
- Support of Wi-Fi direct mode
- IEEE 802.11 PHY data rates of up to 433 Mbps
- Suitable for HD video streaming
- Concurrent multiradio connections
- Wireless Apple CarPlay, Android Auto, Baidu CarLife support
- Hardware encryption engine for 128-bit AES
- WAPI support
- Bluetooth v4.2 with Bluetooth low energy & Bluetooth BR/EDR
- PCM interface for audio
- Climatic, mechanical, and operating life qualification tests according to ISO 16750-4
- AEC-Q100 compliant radio chipset

	EMMY-W161	EMMY-W163	EMMY-W165
<b>Grade</b>			
Automotive	•	•	•
Professional	•	•	•
Standard			
<b>Radio</b>			
Chip inside	NXP 88W8887A		
Bluetooth qualification	v4.2		
Bluetooth profiles	HCI		
Bluetooth BR/EDR	•	•	•
Bluetooth low energy	•	•	•
Wi-Fi IEEE 802.11 standards	a/b/g/n/ac		
Wi-Fi 2.4 / 5 [GHz]	2.4 and 5		
LTE filter	•		
Bluetooth output power conducted [dBm]	10	10	10
Wi-Fi output power conducted [dBm]	18	18	18
Antenna type	1p	2p	1p
<b>OS support</b>			
Android / Linux drivers (from u-blox)	•	•	•
QNX (via third party)	•	•	•
<b>Interfaces</b>			
High-speed UART <sup>a</sup>	1	1	1
SDIO [version]	v3	v3	v3
PCM (Bluetooth audio)	1	1	1
<b>Features</b>			
Micro Access Point [max connects]	10	10	10
AES hardware support	•	•	•
Wi-Fi direct	•	•	•
Factory-assigned MAC address	•	•	•
Factory calibrated RF	•	•	•
Simultaneous STA/AP on different channels	•	•	•

1p = 1 antenna pin for combined Bluetooth and Wi-Fi  
 2p = For Bluetooth only 2p = 2 antenna pins, one each for Bluetooth and Wi-Fi

# EMMY-W1 series



## Features

Wi-Fi standards	IEEE 802.11 a/b/g/n/ac IEEE 802.11 d/e/h/i/k*/r /v*/w
Wi-Fi transfer rates	IEEE 802.11 n/ac: – max. 433 Mbps (80 MHz channel) – max. 200 Mbps (40 MHz channel) – max. 86 Mbps (20 MHz channel) IEEE 802.11 g: 54,48,36,24,18,12,9,6 Mbps IEEE 802.11 b: 11, 5.5, 2, 1 Mbps
Wi-Fi channels	2.4 GHz: 1-13 5 GHz: 36-165 (U-NII band 1, 2, 2e, 3)
Bluetooth	v4.2 (Bluetooth low energy and Bluetooth BR/EDR)
Antennas	EMMY-W161 & EMMY-W165: – 1 combined antenna pin for Bluetooth and Wi-Fi antennas EMMY-W163: – 2 separate antenna pins for Bluetooth and Wi-Fi antennas
LTE filter	Integrated BAW filter (EMMY-W161 only)
Output power	Wi-Fi IEEE 802.11 b: 18 dBm Wi-Fi IEEE 802.11 a/g/n/ac: 16 dBm Bluetooth BR: 10 dBm Bluetooth EDR: 8 dBm

\* Not currently supported by firmware

## Software features

RF parameters	Available in on-board OTP memory
MAC addresses	Available in on-board OTP memory
Security	WEP64 / 128 WPA (TKIP, AES) WPA2 (CCMP, AES) WPA3 WAPI 128-bit AES hardware support
Wi-Fi operational modes	Station (STA): Infrastructure & Direct mode μAP: Supports up to 10 stations Simultaneous STA and μAP Simultaneous dual-band (2.4/5 GHz) Wi-Fi direct One single firmware for Wi-Fi STA, μAP and Bluetooth
Driver support	Free of charge drivers for Linux and Android Third party drivers for QNX
Wi-Fi/Bluetooth coexistence	Internal TDM mechanism

## Interfaces

Wi-Fi	SDIO 3.0 (4-bit, up to 150 MHz clock)
Bluetooth	SDIO 3.0 (4-bit), High-speed UART
Bluetooth audio	PCM

## Package

Dimensions	13.8 × 19.8 × 2.5 mm
Mounting	Solder pins (LGA)

## Environmental data, quality & reliability

Operating temperature	-40 °C to +85 °C
Automotive qualification according to ISO 16750-4	
AEC-Q100 compliant radio chipset	

## Electrical data

RF power supply	3.0 – 3.6 VDC
I/O power supply	3.3 VDC or 1.8 VDC

## Certifications and approvals

Type approvals	Europe (ETSI RED); US (FCC/CFR 47 part 15 unlicensed modular transmitter approval); Canada (IC RSS); Japan (MIC)*; South Korea (KCC)*; Taiwan (NCC)*; Australia/New Zealand (ACMA)*; China (SRRC)*
Bluetooth qualification	v4.2 (Bluetooth BR/EDR and Bluetooth low energy)

\* See the Data Sheet for details

## Support products

The EMMY-W1 evaluation kits include an evaluation board with full access to the module interfaces. The board includes antennas for Wi-Fi and Bluetooth. It also includes U.FL connectors for connecting external Wi-Fi and Bluetooth antennas. The kit has a standard SDIO connector for host communication.

EVK-EMMY-W161	Evaluation kit for EMMY-W161, EMMY-W161-A, EMMY-W165 and EMMY-W165-A
EVK-EMMY-W163	Evaluation kit for EMMY-W163 and EMMY-W163-A

## Product variants

EMMY-W161	Professional grade module with 1 combined antenna pin for Wi-Fi and Bluetooth; integrated LTE filter
EMMY-W163	Professional grade module with 2 separate antenna pins for Wi-Fi and Bluetooth (no LTE filter)
EMMY-W165	Professional grade module with 1 combined antenna pin for Wi-Fi and Bluetooth (no LTE filter)
EMMY-W161-A	Automotive grade module with 1 combined antenna pin for Wi-Fi and Bluetooth; integrated LTE filter
EMMY-W163-A	Automotive grade module with 2 separate antenna pins for Wi-Fi and Bluetooth (no LTE filter)
EMMY-W165-A	Automotive grade module with 1 combined antenna pin for Wi-Fi and Bluetooth (no LTE filter)

## Further information

For contact information, see [www.u-blox.com/contact-us](http://www.u-blox.com/contact-us).

For more product details and ordering information, see the product data sheet.

## Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).  
Copyright © 2020, u-blox AG