

## 2-Port USB/DVI Cable KVM Switch with Audio, Cables and USB Peripheral Sharing

MODEL NUMBER: B032-DUA2



Control 2 computers using one DVI monitor, USB keyboard and USB mouse. Connect a USB 2.0 hub (sold separately) to share USB peripherals, such as printers and hard drives, between computers.

### Features

#### Access and Control 2 Computers with One Keyboard/Mouse/Monitor

- Recommended for home, office, gaming and multimedia applications
- Switch between computers using remote port selector, hotkeys or mouse wheel
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- Listen to audio files on one computer while accessing the other
- Compliant with EDID and HDCP
- Built-in 4-ft. (1.22 m) DVI, USB and audio cables

#### Independent USB 2.0 Peripheral Sharing

- Adding an optional USB hub (sold separately) to the USB console mouse port allows connection of peripherals, such as printers, hard drives, scanners, webcams and thumb drives

#### Flexible Keyboard/Mouse Applications

- Console mouse port emulation/bypass supports most mouse drivers and multifunction mice
- Works with multimedia keyboards and wireless keyboards and mice
- Supports Mac and Sun keyboard emulation

#### Easy Plug-and-Play Setup and Use

- Compatible with Windows, Mac and Linux
- No external power supply, software or drivers to install
- Switches automatically to other computer when one powers off
- Upgradable firmware
- Takes up no valuable desk space

### Highlights

- Built-in 4-ft. (1.22 m) DVI, USB and audio cables
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- Remote, hotkey and mouse port switching
- Compatible with Windows®, Mac® and Linux®

### System Requirements

- DVI monitor
- USB keyboard
- USB mouse
- Computers with DVI and USB ports

### Package Includes

- B032-DUA2 2-Port USB/DVI Cable KVM Switch
- Owner's manual

## Specifications

| <b>OVERVIEW</b>                 |   |
|---------------------------------|---|
| UPC Code                        | 037332200365  |
| Max CPU                         | 2   |
| Technology                      | DVI; Stereo Audio; USB 2.0 (High Speed)               |
| <b>POWER</b>                    |   |
| Power Consumption (Watts)       | 3.05  |
| <b>PHYSICAL</b>                 |   |
| Shipping Dimensions (hwd / in.) | 2.40 x 6.70 x 9.40                                    |
| Shipping Dimensions (hwd / cm)  | 6.10 x 17.02 x 23.88                                  |
| Shipping Weight (lbs.)          | 1.30  |
| Shipping Weight (kg)            | 0.59  |
| Unit Dimensions (hwd / in.)     | 0.000 x 0.000 x 0.000                                 |
| Unit Dimensions (hwd / cm)      | 2.65 x 11.30 x 7.65                                   |
| Unit Weight (lbs.)              | 1.06  |
| Unit Weight (kg)                | 0.48  |
| <b>ENVIRONMENTAL</b>            |   |
| Operating Temperature Range     | 32° to 122°F (0° to 50°C)                             |
| Storage Temperature Range       | -4° to 140°F (-20° to 60°C)                           |
| Relative Humidity               | 0% to 80% RH, Non-Condensing                          |
| <b>COMMUNICATIONS</b>           |   |
| IP Remote Access                | No  |
| <b>CONNECTIONS</b>              |   |
| Number of Ports                 | 2   |
| PC/Server Connections           | DVI; USB  |
| Side A - Connector 1            | DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) |
| Side A - Connector 2            | (2) USB A (FEMALE)                                    |
| Side A - Connector 3            | (3) 3.5MM (FEMALE)                                    |
| Side B - Connector 1            | (2) DVI-D SINGLE LINK (MALE)                          |
| Side B - Connector 2            | (4) USB A (MALE)                                      |

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Side B - Connector 3                 | (4) 3.5MM (MALE)                    |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| NIAP-Certified Secure                | No                                  |
| Number of Users                      | 1                                   |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | 3-year limited warranty             |