


- Continuous short circuit protection
- I/O isolation: 1'060 VAC
- Operating temperature range
-40 to +85 °C without derating
- Input voltage ranges ($\pm 10\%$):
3.3, 5, 12, 24 VDC
- High efficiency up to 82%
- SIP-4 package
- Unregulated outputs
- 3-year product warranty



The TBA 1 is a 1 Watt DC/DC SIP converter series which is specifically designed to offer a low-cost solution with no concession on quality and lifetime. The new design improves on the industry standard features and offers an integrated continuous short circuit protection circuit, an operating temperature range from -40°C to 85°C without derating and I/O-isolation of 1'500 VDC. It offers a broad application range in any space and cost critical application.

| Models | | | | |
|------------|-----------------------------------|---------------------|---------------------|-----------------|
| Order Code | Input Voltage Range | Output Voltage nom. | Output Current max. | Efficiency typ. |
| TBA 1-0310 | 2.97 - 3.63 VDC (3.3 VDC nom.) | 3.3 VDC | 260 mA | 73 % |
| TBA 1-0311 | | 5 VDC | 200 mA | 76 % |
| TBA 1-0510 | 4.5 - 5.5 VDC (5 VDC nom.) | 3.3 VDC | 260 mA | 75 % |
| TBA 1-0511 | | 5 VDC | 200 mA | 79 % |
| TBA 1-0519 | | 9 VDC | 110 mA | 80 % |
| TBA 1-0512 | | 12 VDC | 80 mA | 82 % |
| TBA 1-0513 | | 15 VDC | 65 mA | 82 % |
| TBA 1-1211 | 10.8 - 13.2 VDC (12 VDC nom.) | 5 VDC | 200 mA | 79 % |
| TBA 1-1219 | | 9 VDC | 110 mA | 79 % |
| TBA 1-1212 | | 12 VDC | 80 mA | 80 % |
| TBA 1-1213 | | 15 VDC | 65 mA | 80 % |
| TBA 1-2411 | 21.6 - 26.4 VDC (24 VDC nom.) | 5 VDC | 200 mA | 79 % |
| TBA 1-2419 | | 9 VDC | 110 mA | 80 % |
| TBA 1-2412 | | 12 VDC | 80 mA | 82 % |
| TBA 1-2413 | | 15 VDC | 65 mA | 82 % |

Input Specifications

| | | |
|------------------------|--------------|---|
| Input Current | - At no load | 3.3 Vin models: 30 mA typ. 5 Vin models: 25 mA typ. 12 Vin models: 15 mA typ. 24 Vin models: 10 mA typ. |
| Surge Voltage | | 3.3 Vin models: 5 VDC max. (1 s max.) 5 Vin models: 9 VDC max. (1 s max.) 12 Vin models: 18 VDC max. (1 s max.) 24 Vin models: 30 VDC max. (1 s max.) |
| Recommended Input Fuse | | 3.3 Vin models: 800 mA (slow blow) 5 Vin models: 500 mA (slow blow) 12 Vin models: 200 mA (slow blow) 24 Vin models: 100 mA (slow blow) (The need of an external fuse has to be assessed in the final application.) |
| Input Filter | | Internal Capacitor (add. external 22 µF, ESR <0.1Ω, recommended) |

Output Specifications

| | | |
|--------------------------|---|---|
| Voltage Set Accuracy | | ±3% max. (at 60% for 5VDC models) ±3% max. (at 80% for other models) |
| Regulation | - Input Variation (1% Vin step) - Load Variation | 1.5% max. (see application note: www.tracopower.com/overview/tba1) |
| Ripple and Noise | - 20 MHz Bandwidth | 65 mVp-p typ. 200 mVp-p max. |
| Capacitive Load | | 3.3 Vout models: 3'300 µF max. 5 Vout models: 2'200 µF max. 9 Vout models: 1'000 µF max. 12 Vout models: 470 µF max. 15 Vout models: 470 µF max. |
| Minimum Load | | 10 % of Iout max. |
| Temperature Coefficient | | ±0.02 %/K max. |
| Start-up Time | | 30 ms max. |
| Short Circuit Protection | | Continuous, Automatic recovery |

Safety Specifications

| | | |
|------------------|-----------------------------|---|
| Safety Standards | - IT / Multimedia Equipment | Designed for EN 62368-1 (no certification) |
|------------------|-----------------------------|---|

General Specifications

| | | |
|------------------------|--|---|
| Relative Humidity | | 95% max. (non condensing) |
| Temperature Ranges | - Operating Temperature - Case Temperature - Storage Temperature | -40°C to +95°C +105°C max. -55°C to +125°C |
| Power Derating | - High Temperature | 5 %/K above 85°C |
| Cooling System | | Natural convection (20 LFM) |
| Switching Frequency | | 50 - 200 kHz (PWM) |
| Insulation System | | Functional Insulation |
| Isolation Test Voltage | - Input to Output, 60 s | 1'500 VDC |
| Isolation Resistance | - Input to Output, 500 VDC | 1'000 MΩ min. |
| Isolation Capacitance | - Input to Output, 100 kHz, 1 V | 30 pF max. |
| Reliability | - Calculated MTBF | 2'000'000 h (MIL-HDBK-217F, ground benign) |
| Housing Material | | Plastic (UL 94 V-0 rated) |
| Potting Material | | Epoxy (UL 94 V-0 rated) |
| Pin Material | | Nickel-Iron (Alloy 42) |

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

