



NOTES:

- CABLE: UL20276 USB REV. 3.0 CABLE. (1P\*28AWG+D+AL-MYLAR)\*2C+1P\*28AWG+2C\*24AWG+AL+DRAIN+BRAID(AL), BLUE PVC JACKET.  
OD: 5.5±0.15mm.Voltage rating:30V, VW-1.
- CONNECTOR: P1:USB 3.0 REV. A TYPE MALE, BLUE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.  
P2: USB 3.0 A TYPE FEMALE, BLUE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
- 071D MOUDLE: BLACK PC+ABS.
- HOOD: P1: MOLDED 45P BLACK PVC;  
P2: MOLDED 25P BLACK PVC.
- TESTING: 100% ELECTRICAL TESTING.
- Temperature:0°C~50°C for operating; -20°C~60°C for storage.  
Relative Humifity:10% -90%, non-condensing.

\*\* MODEL AND SKU NAME TO BE OBTAINED FROM PCM PRIOR TO PRODUCTION



B	Remove USB3.0 LOGO		03/18/20	
A	INITIAL RELEASE		08/22/15	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE				
INCHES				
M/M				
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	REV B	
DRAWN BY	BOBO		SHEET	1/1
			DATE	03/18/20
CHECK BY			DWG NO.	993754
APPD BY			TITLE	USB 3.0 AM TO USB3.0 AF
			PART NO.	U324-001-APM