



Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ Thread			d ₃	h	t
1.25 31.8	10 x 32	1/4 x 20	-	0.50 12.7	0.88 22.4	0.38 9.7
1.50 38.1	1/4 x 20	-	-	0.63 16.0	1.00 25.4	0.38 9.7
1.50 38.1	5/16 x 18	3/8 x 16	-	0.63 16.0	1.00 25.4	0.50 12.7
2.00 50.8	1/4 x 20	5/16 x 18	3/8 x 16	0.88 22.4	1.00 25.4	0.50 12.7
3.00 76.2	5/16 x 18	-	-	0.88 22.4	1.13 28.7	0.50 12.7

Specification

- Hand knob d₁ = 1.50 / 2.00 / 3.00"
Phenolic plastic
 - Temperature resistant up to 300 °F (149 °C)
 - Black, shiny finish
- Hand knob d₁ = 1.25"
Nylon plastic
 - Temperature resistant up to 200 °F (93 °C)
 - Black, matte finish
- Tapped insert
Brass
- *Plastic Characteristics* → page 2135
- **RoHS compliant**

On request

- Additional thread sizes

Information

FPK hand knobs are a popular choice for light duty finger tightening applications.
 see also...
 • *Hand Knobs FPKS (with Steel Threaded Stud)* → page 639

How to order ¹ ² FPK-1.50-5/16X18	1 Handle diameter d ₁
	2 Thread d ₂