



SS Stainless Steel

4 Type

A 2x2 Bores for countersunk head screws

5 Identification no.

- 1 Fixed bearing (Pin) right
- 2 Fixed bearing (Pin) left

Metric table

Dimensions in: millimeters - inches

2 l_1	3 l_2	d_1	d_2	h_1	h_2	h_3	$h_4 +0.5$	l_3	m_1	m_2
40 1.57	40 1.57	5.3 0.21	4 0.16	9 0.35	5 0.20	5.5 0.22	11 0.43	16 0.63	25 0.98	25 0.98
50 1.97	50 1.97	6.4 0.25	6 0.24	11.5 0.45	6 0.24	6.5 0.26	13 0.51	21 0.83	30 1.18	30 1.18
60 2.36	60 2.36	8.3 0.33	8 0.31	15 0.59	8 0.31	8.5 0.33	17 0.67	26 1.02	36 1.42	36 1.42

Specification

- Body
 - Zinc die-cast **ZD**
 - Powder coated **SW**
 - Silver, RAL 9006, textured finish **SR**
 - Stainless steel **NI**
 - European Standard No. 1.4308 (AISI CF-8)
 - Matte shot-blasted finish **GS**
- Pin
 - Stainless steel
 - European Standard No. 1.4305 (AISI 303)
- RoHS compliant

Information

- see also...
- List of Hinge Types
 - Hinges GN 237 (Zinc Die-Cast, Countersunk Thru Holes or Threaded Stud Type)
 - Spacer Plates GN 2370
 - Spacer Plates with Tapped Holes GN 2372
 - Limit Stops GN 2374

How to order	1 Material
	2 Width l_1
	3 Length l_2
	4 Type
	5 Identification no.
	6 Finish

1 2 3 4 5 6
GN 337-ZD-40-40-A-1-SR

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10