



Pre-set at factory to desired value within a +/- 4% tolerance. When preset torque value is achieved, a distinct click is felt and heard, followed by a sudden release into several degrees of free movement. Ideal for applications in which one torque value is used extensively. Compact design makes these tools invaluable in hard to reach locations. Tools automatically reset when torquing- force is removed.

Material and Plating

Connector parts

	Material	Plating
Handle	Stainless steel	n.a.
Head 22mm	Stainless steel	n.a.

Mechanical Data

Wrench size	11mm
Torque setting	1.5 Nm

Weight

388 g/pc

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
F. Fraunhofer	08.03.2017	Chr. Janßen	24.02.2021	b00	20-1927	B. Wollitzer	24.02.2021
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.com						Tel. : +49 8684 18-0 Email : info@rosenberger.com	
							Page 1 / 1